

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Zink® 80/81**

Revision date: 26.08.2022

Product code: 2999

Page 1 of 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

WS-Zink® 80/81

UFI: F4V5-79JQ-SVJ5-QPVF

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**industrial paint  
Paint, Varnish.**Uses advised against**

Do not use for products which come into contact with the food stuffs.

**1.3. Details of the supplier of the safety data sheet**

Company name:	W+S GmbH Lackchemie und Aerosol-Technik	
Street:	Am Sportplatz 5	
Place:	D-63791 Karlstein-Dettingen	
Telephone:	+49 6188 9575-0	Telefax: +49 6188 9575-30
e-mail:	info@ws-lackchemie.de	
Responsible Department:	Abt. Produkt / Sicherheit	

**1.4. Emergency telephone number:** +49 551-19240 GIZ-Nord Poisons Centre**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**Hazard categories:  
Flammable liquid: Flam. Liq. 3  
Hazardous to the aquatic environment: Aquatic Acute 1  
Hazardous to the aquatic environment: Aquatic Chronic 1  
Hazard Statements:  
Flammable liquid and vapour.  
Very toxic to aquatic life with long lasting effects.**2.2. Label elements****GB CLP Regulation****Signal word:** Warning**Pictograms:****Hazard statements**H226 Flammable liquid and vapour.  
H410 Very toxic to aquatic life with long lasting effects.**Precautionary statements**P273 Avoid release to the environment.  
P370+P378 In case of fire: In case of fire, use sand, extinguishing powder or alcohol resistant foam.  
P501 Dispose of contents/container to Offer surplus and non-recyclable solutions to a licensed disposal company..**Special labelling of certain mixtures**

EUH208 Contains maleic anhydride, 2,2'-iminodiethylamine; diethylenetriamine. May produce an

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Zink® 80/81**

Revision date: 26.08.2022

Product code: 2999

Page 2 of 9

allergic reaction.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Chemical characterization**

Paint, Varnish.

**Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
7440-66-6	zinc powder - zinc dust (stabilised)			50-75 %
	231-175-3	030-001-01-9		
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
64742-95-6	Lösungsmittelnaphta, leichte aromatische, Benzolgehalt <0,1%			10-20 %
	265-199-0			
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
1330-20-7	xylene			1-5 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. Limits, M-factors and ATE			
64742-95-6	265-199-0	Lösungsmittelnaphta, leichte aromatische, Benzolgehalt <0,1%	10-20 %	
	inhalation: LC50 = 5,2 mg/l (vapours); dermal: LD50 = 3160 mg/kg; oral: LD50 = 2000 mg/kg			
1330-20-7	215-535-7	xylene	1-5 %	
	inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg			

**Further Information**

Full text of R-phrases: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Give nothing to eat or drink.

**After inhalation**

In case of inhaling spray mists, consult a doctor immediately and show him box or label. If victim is at risk of losing consciousness, position and transport on their side. Provide fresh air.

**After contact with skin**

After contact with skin, wash immediately with: Water. Remove contaminated, saturated clothing immediately. Change contaminated clothing. Wash thoroughly the body (shower or bath).

**After contact with eyes**

Rinse immediately carefully and thoroughly with eye-bath or water. If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Zink® 80/81**

Revision date: 26.08.2022

Product code: 2999

Page 3 of 9

**After ingestion**

If swallowed, immediately drink: Water. Do NOT induce vomiting. Call a physician immediately.  
Caution if victim vomits: Risk of aspiration!

**4.2. Most important symptoms and effects, both acute and delayed**

Vapours may cause drowsiness and dizziness. Frequently or prolonged contact with skin may cause dermal irritation.

**4.3. Indication of any immediate medical attention and special treatment needed**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Foam. Dry extinguishing powder. Carbon dioxide (CO<sub>2</sub>). ABC powder.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Burning produces heavy smoke. In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Suppress gases/vapours/mists with water spray jet. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation. Remove all sources of ignition. Provide adequate ventilation. See protective measures under point 7 and 8.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

**6.3. Methods and material for containment and cleaning up****Other information**

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

See protective measures under point 7 and 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Preventive measures: If handled uncovered, arrangements with local exhaust ventilation have to be used. It is recommended to design all work processes always so that the following is excluded: inhalation. skin contact. Eye contact. Take precautionary measures against static discharges.

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Zink® 80/81**

Revision date: 26.08.2022

Product code: 2999

Page 4 of 9

**Advice on protection against fire and explosion**

Vapours may form explosive mixtures with air.

**Advice on general occupational hygiene**

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.  
Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Keep only in the original container in a cool, well-ventilated place. Take precautionary measures against static discharges.

**Hints on joint storage**

Materials to avoid: Acid. Base. Material, combustible. Oxidizing agents.

**Further information on storage conditions**

Keep away from sources of ignition - No smoking. Protect against: heat. Keep/Store only in original container.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
7429-90-5	Aluminium metal, respirable dust	-	4		TWA (8 h)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

**Biological Monitoring Guidance Values (EH40)**

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

**8.2. Exposure controls****Appropriate engineering controls**

Occupational exposure controls: Refer to chapter 7. No further action is necessary.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Suitable eye protection: Framed glasses. Goggles.

**Hand protection**

Tested protective gloves are to be worn:  
Suitable material: NBR (Nitrile rubber), Butyl rubber.  
Thickness of glove material: >0,4mm  
penetration time (maximum wearing period): >480min  
DIN-/EN-Norms: EN ISO 374

**Skin protection**

Suitable protective clothing: Lab apron.

**Respiratory protection**

Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation. insufficient absorption.

**Environmental exposure controls**

Refer to chapter 7 No further action is necessary.

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Zink® 80/81**

Revision date: 26.08.2022

Product code: 2999

Page 5 of 9

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	silver grey
Odour:	characteristic
Odour threshold:	not determined

**Changes in the physical state**

Boiling point or initial boiling point and boiling range:	145 °C
Flash point:	35 °C
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	7,8 vol. %
Auto-ignition temperature:	205 °C
Flow time:	600 (3 mm)
Vapour pressure: (at 20 °C)	2,1 hPa
Density:	2,142 g/cm <sup>3</sup>

**9.2. Other information****Other safety characteristics**

Solvent content:	VOCV (CH): 23,204 % VOC (EU): 496,937 g/l
Solid content:	76,8 %

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

**10.2. Chemical stability**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

**10.3. Possibility of hazardous reactions**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

**10.4. Conditions to avoid**

Conditions to avoid:  
In case of warming: Danger of bursting container.

**10.5. Incompatible materials**

Alkalis (alkalis). Acid. Oxidizing agents.

**10.6. Hazardous decomposition products**

Thermal decomposition can lead to the escape of irritating gases and vapors.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Toxicological data are not available.

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Zink® 80/81**

Revision date: 26.08.2022

Product code: 2999

Page 6 of 9

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-95-6	Lösungsmittelnaphta, leichte aromatische, Benzolgehalt <0,1%				
	oral	LD50 2000 mg/kg	Rat		
	dermal	LD50 3160 mg/kg	Rabbit.		
	inhalation (4 h) vapour	LC50 5,2 mg/l	Rat		
1330-20-7	xylene				
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

**Irritation and corrosivity**

Evaluation: Not an irritant.

**STOT-repeated exposure**

Has de-greasing effect on the skin.

**Specific effects in experiment on an animal**

Rat LD50: 4300 - 5800 mg/kg Acute toxicity, oral

Data apply to the main component.

**Additional information on tests**

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

**Further information**

Toxicological data are not available.

**SECTION 12: Ecological information****12.1. Toxicity**

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Doesn't get into the sewage water as long as the process is carried out according to regulations.

Very toxic for Water fleas.

**12.2. Persistence and degradability**

No data available

**12.3. Bioaccumulative potential**

No data available

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

No data available

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No data available

**Further information**

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Zink® 80/81**

Revision date: 26.08.2022

Product code: 2999

Page 7 of 9

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

**List of Wastes Code - residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - used product**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Hand over to officially registered waste disposal company.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number or ID number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	PAINT or PAINT RELATED MATERIAL
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3



Classification code:	F1
Special Provisions:	163 640E 650
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	30
Tunnel restriction code:	D/E

**Other applicable information (land transport)**

: 163 640E 650  
: 3  
E1

**Inland waterways transport (ADN)**

<b>14.1. UN number or ID number:</b>	UN 1263
<b>14.2. UN proper shipping name:</b>	Paint
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	III
Hazard label:	3

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Zink® 80/81**

Revision date: 26.08.2022

Product code: 2999

Page 8 of 9



Classification code: F1  
Special Provisions: 163 367 650  
Limited quantity: 5 L  
Excepted quantity: E1  
**Other applicable information (inland waterways transport)**  
: 163 640E 650

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1263  
**14.2. UN proper shipping name:** PAINT  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: 163, 223, 367, 955  
Limited quantity: 5 L  
Excepted quantity: E1  
EmS: F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number or ID number:** UN 1263  
**14.2. UN proper shipping name:** PAINT  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Special Provisions: A3 A72 A192  
Limited quantity Passenger: 10 L  
Passenger LQ: Y344  
Excepted quantity: E1  
IATA-packing instructions - Passenger: 355  
IATA-max. quantity - Passenger: 60 L  
IATA-packing instructions - Cargo: 366  
IATA-max. quantity - Cargo: 220 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: zinc powder - zinc dust (stabilised)

**14.6. Special precautions for user**

No information available.

**14.7. Maritime transport in bulk according to IMO instruments**

No information available.

**SECTION 15: Regulatory information**



**Safety Data Sheet**

according to UK REACH Regulation

**WS-Zink® 80/81**

Revision date: 26.08.2022

Product code: 2999

Page 9 of 9

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

2004/42/EC (VOC):

VOCV (CH): 23,204 %

VOC (EU): 496,937 g/l

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information****Relevant H and EUH statements (number and full text)**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains maleic anhydride, 2,2'-iminodiethylamine; diethylenetriamine. May produce an allergic reaction.

**Further Information**

The product is classified and labelled according to EC directives or corresponding national laws.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*