

**Safety Data Sheet**

according to UK REACH Regulation

WS-Teflon-Spray

Revision date: 13.03.2025

Product code: 3633

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

WS-Teflon-Spray

UFI: RAW5-A979-2VJ3-YG1C

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricant, lubricants and release products

Uses advised against

Do not use for products which come into contact with the food stuffs.

1.3. Details of the supplier of the safety data sheet

Company name:	W+S GmbH Lackchemie und Aerosol-Technik	
Street:	Am Sportplatz 5	
Place:	D-63791 Karlstein-Dettingen	
Telephone:	+49 6188 9575-0	Telefax: +49 6188 9575-30
E-mail:	info@ws-lackchemie.de	
Contact person:	Abt. Produkt / Sicherheit	
Responsible Department:	Abt. Produkt / Sicherheit	

1.4. Emergency telephone number: +49 551-19240 GIZ-Nord Poisons Centre

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard categories:
Aerosols: Aerosol 1
Hazard Statements:
Extremely flammable aerosol.
Pressurised container: May burst if heated.

2.2. Label elements**GB CLP Regulation**

Signal word: Danger

Pictograms:

**Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P102	Keep out of reach of children.

**Safety Data Sheet**

according to UK REACH Regulation

WS-Teflon-Spray

Revision date: 13.03.2025

Product code: 3633

Page 2 of 8

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Aerosole

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-31-0	Distillates (petroleum), chemically neutralized light; Kerosine - unspecified			50 - < 55 %
	265-132-5	649-421-00-7		
	Asp. Tox. 1; H304			
74-98-6	propane			50-100 %
	200-827-9	601-003-00-5		
	Flam. Gas 1; H220			
106-97-8	butane			50-100 %
	203-448-7	601-004-00-0		
	Flam. Gas 1; H220			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
106-97-8	203-448-7	butane	50-100 %
	inhalation: LC50 = 658 ppm (gases)		

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). No administration in cases of unconsciousness or cramps.

After inhalation

Provide fresh air. Put victim at rest, cover with a blanket and keep warm. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes. Wash thoroughly the body (shower or bath). After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Call a physician immediately. Do NOT induce vomiting. Give nothing to eat or drink.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**Safety Data Sheet**

according to UK REACH Regulation

WS-Teflon-Spray

Revision date: 13.03.2025

Product code: 3633

Page 3 of 8

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Foam. Dry extinguishing powder. Carbon dioxide (CO₂).**Unsuitable extinguishing media**

High power water jet.

5.2. Special hazards arising from the substance or mixture

Heating causes rise in pressure with risk of bursting. Combustible. Vapours may form explosive mixtures with air. Special exposure hazards arising from the substance itself, combustion products, resulting gases: Nitrogen oxides (NO_x). Carbon monoxide

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard. Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Information for safe handling: If handled uncovered, arrangements with local exhaust ventilation have to be used. The following must be prevented: inhalation. skin contact. Eye contact.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges.

Only use the material in places where open light, fire and other flammable sources can be kept away. Keep only in the original container in a cool, well-ventilated place.

**Safety Data Sheet**

according to UK REACH Regulation

WS-Teflon-Spray

Revision date: 13.03.2025

Product code: 3633

Page 4 of 8

Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing. Materials to avoid: Acid. Base. Oxidizing agents. Paper.

Further information on storage conditions

Store only in original container. Protect against: heat. Heating causes rise in pressure with risk of bursting.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Additional advice on limit values

source:

8.2. Exposure controls**Appropriate engineering controls**

Refer to chapter 7. No further action is necessary.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Goggles.

Hand protection

Tested protective gloves are to be worn:

Suitable material: NBR (Nitrile rubber), Butyl rubber.

Thickness of glove material: >0,4mm

penetration time (maximum wearing period): >480min

DIN-/EN-Norms EN ISO 374

Skin protection

Additional body protection measures: Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. Do not eat, drink, smoke or sneeze at the workplace. Avoid contact with skin, eyes and clothes. Wash hands before breaks and after work. Set out skin protection guidelines.

Respiratory protection

Filtering device (full mask or mouthpiece) with filter:

Environmental exposure controls

Refer to chapter 7 No further action is necessary.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	characteristic
Odour:	characteristic
Odour threshold:	not determined

Test method

Boiling point or initial boiling point and boiling range:	-42 °C
Lower explosion limits:	1,5 vol. %
Upper explosion limits:	9,35 vol. %
Flash point:	-25 °C DIN EN ISO 1523

**Safety Data Sheet**

according to UK REACH Regulation

WS-Teflon-Spray

Revision date: 13.03.2025

Product code: 3633

Page 5 of 8

Auto-ignition temperature: 273 °C DIN 51794
Vapour pressure: 3,2 hPa DIN EN 12
(at 20 °C)
Density: 0,74 g/cm³

9.2. Other information**Information with regard to physical hazard classes**

Self-ignition temperature

Gas:

Propan / Butan

Other safety characteristics

Solvent content:

91,3 %

VOC value 678,13

SECTION 10: Stability and reactivity**10.1. Reactivity**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.2. Chemical stability

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.3. Possibility of hazardous reactions

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard. Danger of bursting container.

10.5. Incompatible materials

Reacts with : Alkalis (alkalis). Oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Propan LC50: 56 - 80 Vol.-% (Rat , 15 min.)

Dimethylether LC50: 308 mg/L (Rat)

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
106-97-8	butane				
	inhalation (4 h) gas	LC50	658 ppm	Rat	GESTIS

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

STOT-repeated exposure

Can cause frostbite. Has de-greasing effect on the skin.

Specific effects in experiment on an animal

Toxicological data are not available.

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

**Safety Data Sheet**

according to UK REACH Regulation

WS-Teflon-Spray

Revision date: 13.03.2025

Product code: 3633

Page 6 of 8

SECTION 12: Ecological information**12.1. Toxicity**

Aquatic toxicity

Harmful for Water fleas.

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
74-98-6	propane	2,36
106-97-8	butane	2,89

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

No data available

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC). Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 1950

14.2. UN proper shipping name:

AEROSOLS

**Safety Data Sheet**

according to UK REACH Regulation

WS-Teflon-Spray

Revision date: 13.03.2025

Product code: 3633

Page 7 of 8

14.3. Transport hazard class(es):

2

14.4. Packing group:

-

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

Excepted quantity:

E0

Transport category:

2

Tunnel restriction code:

D

Other applicable information (land transport)

: 190 - 327 - 625

: 2

: D

Inland waterways transport (ADN)**14.1. UN number or ID number:**

UN 1950

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2

14.4. Packing group:

-

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

Excepted quantity:

E0

Other applicable information (inland waterways transport)

: 190 327 625

Marine transport (IMDG)**14.1. UN number or ID number:**

UN 1950

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

Hazard label:

2.1



Special Provisions:

63, 190, 277, 327, 344, 381, 959

Limited quantity:

1000 mL

Excepted quantity:

E0

EmS:

F-D, S-U

Other applicable information (marine transport)

: 63, 190, 277, 327, 959

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:**

UN 1950

14.2. UN proper shipping name:

AEROSOLS, FLAMMABLE

14.3. Transport hazard class(es):

2.1

14.4. Packing group:

-

Hazard label:

2.1

**Safety Data Sheet**

according to UK REACH Regulation

WS-Teflon-Spray

Revision date: 13.03.2025

Product code: 3633

Page 8 of 8



Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg
Other applicable information (air transport)
: A1

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40

Directive 2004/42/EC on VOC in 91,3 %
paints and varnishes: VOC value 678,13

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Abbreviations and acronyms**

Flam. Gas: Flammable gases

Asp. Tox: Aspiration hazard

Relevant H and EUH statements (number and full text)

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)