

**Safety Data Sheet**

according to UK REACH Regulation

WS-Lackspray. verschiedenfarbig

Revision date: 13.03.2025

Product code: 9001

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

WS-Lackspray. verschiedenfarbig

UFI: 6N26-Q90W-1VJS-YN5C

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

industrial paint

Paint, Varnish.

Uses advised against

Do not use for products which come into contact with the food stuffs.

1.3. Details of the supplier of the safety data sheet

Company name: W+S GmbH Lackchemie und Aerosol-Technik

Street: Am Sportplatz 5

Place: D-63791 Karlstein-Dettingen

Telephone: +49 6188 9575-0

Telefax: +49 6188 9575-30

E-mail: info@ws-lackchemie.de

Contact person: Abt. Produkt / Sicherheit

Responsible Department: Abt. Produkt / Sicherheit

1.4. Emergency telephone number:

+49 551-19240 GIZ-Nord Poisons Centre

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard categories:

Aerosols: Aerosol 3

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

acetone; propan-2-one; propanone

n-butyl acetate

ethyl acetate

Signal word:

Danger

Pictograms:**Hazard statements**

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H319

Causes serious eye irritation.

**Safety Data Sheet**

according to UK REACH Regulation

WS-Lackspray. verschiedenfarbig

Revision date: 13.03.2025

Product code: 9001

Page 2 of 9

H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P261 Avoid breathing Gas/fumes/vapour/spray.

P271 Use only outdoors or in a well-ventilated area.

P102 Keep out of reach of children.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Aerosole

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
115-10-6	dimethyl ether			45 - < 50 %
	204-065-8	603-019-00-8		
	Flam. Gas 1; H220			
67-64-1	acetone; propan-2-one; propanone			10 - < 15 %
	200-662-2	606-001-00-8		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
141-78-6	ethyl acetate			10 - < 15 %
	205-500-4	607-022-00-5		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
123-86-4	n-butyl acetate			10 - < 15 %
	204-658-1	607-025-00-1		
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
64742-95-6	Lösemittelnaphta (Erdöl), Benzolgehalt < 0,1%			1 - < 5 %
	Flam. Liq. 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H304 H411			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
67-64-1	200-662-2	acetone; propan-2-one; propanone	10 - < 15 %
		inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 20000 mg/kg; oral: LD50 = 5800 mg/kg	
64742-95-6		Lösemittelnaphta (Erdöl), Benzolgehalt < 0,1%	1 - < 5 %
		dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000 mg/kg	

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). No administration in cases of unconsciousness or cramps.

**Safety Data Sheet**

according to UK REACH Regulation

WS-Lackspray. verschiedenfarbig

Revision date: 13.03.2025

Product code: 9001

Page 3 of 9

After inhalation

Put victim at rest, cover with a blanket and keep warm. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

Take off immediately all contaminated clothing, including underwear and shoes. Wash thoroughly the body (shower or bath). After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Call a physician immediately. Do NOT induce vomiting. Give nothing to eat or drink.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam. Dry extinguishing powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Heating causes rise in pressure with risk of bursting. Combustible. Vapours may form explosive mixtures with air. Special exposure hazards arising from the substance itself, combustion products, resulting gases: Nitrogen oxides (NO_x). Carbon monoxide

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage

**Safety Data Sheet**

according to UK REACH Regulation

WS-Lackspray. verschiedenfarbig

Revision date: 13.03.2025

Product code: 9001

Page 4 of 9

7.1. Precautions for safe handling**Advice on safe handling**

Information for safe handling: If handled uncovered, arrangements with local exhaust ventilation have to be used. The following must be prevented: inhalation. skin contact. Eye contact.

Advice on protection against fire and explosion

Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Take precautionary measures against static discharges.

Only use the material in places where open light, fire and other flammable sources can be kept away. Keep only in the original container in a cool, well-ventilated place.

Hints on joint storage

Materials to avoid: Acid. Base. Oxidizing agents. Paper.

Further information on storage conditions

Store only in original container. Protect against: heat. Heating causes rise in pressure with risk of bursting.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
115-10-6	Dimethyl ether	400	766		TWA (8 h)	WEL
		500	958		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	734		TWA (8 h)	WEL
		400	1468		STEL (15 min)	WEL

Additional advice on limit values

source:

8.2. Exposure controls**Appropriate engineering controls**

Refer to chapter 7. No further action is necessary.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Goggles.

Hand protection

Tested protective gloves are to be worn:

Suitable material: NBR (Nitrile rubber). , Butyl rubber.

Thickness of glove material: >0,4mm

penetration time (maximum wearing period): >480min

DIN-/EN-Norms EN ISO 374

**Safety Data Sheet**

according to UK REACH Regulation

WS-Lackspray. verschiedenfarbig

Revision date: 13.03.2025

Product code: 9001

Page 5 of 9

Skin protection

Additional body protection measures: Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. Do not eat, drink, smoke or sneeze at the workplace. Avoid contact with skin, eyes and clothes. Wash hands before breaks and after work. Set out skin protection guidelines.

Respiratory protection

Filtering device (full mask or mouthpiece) with filter:

Environmental exposure controls

Refer to chapter 7 No further action is necessary.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol
Colour:	characteristic
Odour:	characteristic
Odour threshold:	not determined

Test method

Boiling point or initial boiling point and boiling range:	-25 °C
Lower explosion limits:	1,2 vol. %
Upper explosion limits:	13,8 vol. %
Flash point:	-25 °C DIN EN ISO 1523
Auto-ignition temperature:	273 °C DIN 51794
Vapour pressure: (at 20 °C)	3,2 hPa DIN EN 12
Density:	0,826 g/cm ³ DIN 53217

9.2. Other information**Other safety characteristics**

Solvent content:	83,2 %
	VOC value 687,23
Solid content:	16,8 %

SECTION 10: Stability and reactivity**10.1. Reactivity**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.2. Chemical stability

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.3. Possibility of hazardous reactions

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.4. Conditions to avoid

heat. Heating causes rise in pressure with risk of bursting.

10.5. Incompatible materials

Reacts with : Alkalis (alkalis). Oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation**

**Safety Data Sheet**

according to UK REACH Regulation

WS-Lackspray. verschiedenfarbig

Revision date: 13.03.2025

Product code: 9001

Page 6 of 9

Acute toxicity

Propan LC50: 56 - 80 Vol.-% (Rat , 15 min.)

Dimethylether LC50: 308 mg/L (Rat)

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	oral	LD50 mg/kg	5800	Rat	RTECS	
	dermal	LD50 mg/kg	20000	Rabbit	IUCLID	
	inhalation (4 h) vapour	LC50	76 mg/l	Rat		
64742-95-6	Lösemittelnaphta (Erdöl), Benzolgehalt < 0,1%					
	oral	LD50 mg/kg	>2000	Rat		
	dermal	LD50 mg/kg	>2000	Rabbit		

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

STOT-repeated exposure

Can cause frostbite. Has de-greasing effect on the skin.

Specific effects in experiment on an animal

Toxicological data are not available.

SECTION 12: Ecological information**12.1. Toxicity**

Aquatic toxicity

Harmful for Water fleas.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone					
	Acute fish toxicity	LC50 mg/l	5540	96 h Onchorhynchus mykiss		
	Acute crustacea toxicity	EC50 mg/l	6100	48 h Daphnia magna		

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
115-10-6	dimethyl ether	0,1
67-64-1	acetone; propan-2-one; propanone	-0,24

12.4. Mobility in soil

No data available

**Safety Data Sheet**

according to UK REACH Regulation

WS-Lackspray. verschiedenfarbig

Revision date: 13.03.2025

Product code: 9001

Page 7 of 9

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

No data available

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0
Transport category: 2
Tunnel restriction code: D

Other applicable information (land transport)

: 190 - 327 - 625
: 2
: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1

**Safety Data Sheet**

according to UK REACH Regulation

WS-Lackspray. verschiedenfarbig

Revision date: 13.03.2025

Product code: 9001

Page 8 of 9



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Other applicable information (inland waterways transport)

: 190 327 625

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 381, 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Other applicable information (marine transport)

: 63, 190, 277, 327, 959

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, FLAMMABLE
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)

: A1

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

**Safety Data Sheet**

according to UK REACH Regulation

WS-Lackspray. verschiedenfarbig

Revision date: 13.03.2025

Product code: 9001

Page 9 of 9

Directive 2004/42/EC on VOC in
paints and varnishes: 83,2 %
VOC value 687,23

Marketing and use of explosives precursors (Regulation (EU) 2019/1148):

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Abbreviations and acronyms**

Flam. Gas: Flammable gases
Flam. Liq: Flammable liquids
Asp. Tox: Aspiration hazard
Eye Irrit: Eye irritation
STOT SE: Specific target organ toxicity - single exposure
Aquatic Chronic: Chronic aquatic hazard

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)