

**Safety Data Sheet**

according to UK REACH Regulation

WS-Plast® Dickschicht M 4200

Revision date: 13.03.2025

Product code: 1000

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

WS-Plast® Dickschicht M 4200

UFI: N000-50S6-S007-URKT

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**Paint, Varnish.
industrial paint**Uses advised against**

Do not use for products which come into contact with the food stuffs.

1.3. Details of the supplier of the safety data sheet

Company name: W+S GmbH Lackchemie und Aerosol-Technik
Street: Am Sportplatz 5
Place: D-63791 Karlstein-Dettingen
Telephone: +49 6188 9575-0
E-mail: info@ws-lackchemie.de
Contact person: Abt. Produkt / Sicherheit
Responsible Department: Abt. Produkt / Sicherheit

Telefax: +49 6188 9575-30

1.4. Emergency telephone number:

+49 551-19240 GIZ-Nord Poisons Centre

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Flam. Liq. 3; H226
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT RE 2; H373
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Signal word:** Warning**Pictograms:****Hazard statements**

H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271 Use only outdoors or in a well-ventilated area.

**Safety Data Sheet**

according to UK REACH Regulation

WS-Plast® Dickschicht M 4200

Revision date: 13.03.2025

Product code: 1000

Page 2 of 12

P273 Avoid release to the environment.
P370+P378 In case of fire: Use sand, dry chemical or alcohol-resistant foam to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P234 Keep only in original packaging.

Special labelling of certain mixtures

EUH208 Contains n-butyl acrylate. May produce an allergic reaction.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
1330-20-7	xylene			15 - < 20 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			
108-65-6	2-methoxy-1-methylethyl acetate			5 - < 10 %
	203-603-9	607-195-00-7		
	Flam. Liq. 3; H226			
64742-95-6	Lösungsmittelnaphta, leichte aromatische, Benzolgehalt <0,1%			5 - < 10 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
100-41-4	ethylbenzene			5 - < 10 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol			5 - < 10 %
	204-626-7	603-016-00-1		
	Eye Irrit. 2; H319			
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether			5 - < 10 %
	203-539-1	603-064-00-3		
	Flam. Liq. 3, STOT SE 3; H226 H336			
141-32-2	n-butyl acrylate			< 1 %
	205-480-7	607-062-00-3		
	Flam. Liq. 3, Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3; H226 H315 H319 H317 H335			
13463-67-7	titanium dioxide			< 1 %
	236-675-5	022-006-00-2		
	Carc. 2; H351			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

WS-Plast® Dickschicht M 4200

Revision date: 13.03.2025

Product code: 1000

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1330-20-7	215-535-7	xylene	15 - < 20 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg	
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	5 - < 10 %
		dermal: LD50 = 7500 mg/kg; oral: LD50 = 8532 mg/kg	
64742-95-6	918-668-5	Lösungsmittelnaphta, leichte aromatische, Benzolgehalt <0,1%	5 - < 10 %
		inhalation: LC50 = 5,2 mg/l (vapours); dermal: LD50 = 3160 mg/kg; oral: LD50 = 2000 mg/kg	
100-41-4	202-849-4	ethylbenzene	5 - < 10 %
		inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg	
123-42-2	204-626-7	4-hydroxy-4-methylpentan-2-one; diacetone alcohol	5 - < 10 %
		dermal: LD50 = 13630 mg/kg; oral: LD50 = 2520 mg/kg Eye Irrit. 2; H319: >= 10 - 100	
107-98-2	203-539-1	1-methoxy-2-propanol; monopropylene glycol methyl ether	5 - < 10 %
		dermal: LD50 = 11000 mg/kg; oral: LD50 = > 5000 mg/kg	

Further Information

Full text of R-phrases: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Give nothing to eat or drink.

After inhalation

In case of inhaling spray mists, consult a doctor immediately and show him box or label. If victim is at risk of losing consciousness, position and transport on their side. Provide fresh air.

After contact with skin

Remove contaminated, saturated clothing immediately. Change contaminated clothing. Wash thoroughly the body (shower or bath).

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam. Dry extinguishing powder. Carbon dioxide (CO₂). ABC powder.

Unsuitable extinguishing media

High power water jet.

**Safety Data Sheet**

according to UK REACH Regulation

WS-Plast® Dickschicht M 4200

Revision date: 13.03.2025

Product code: 1000

Page 4 of 12

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately.

Additional information

Contaminated fire-fighting water must be collected separately. Remove product from area of fire. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment. See protective measures under point 7 and 8.

6.2. Environmental precautions

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**Other information**

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

It is recommended to design all work processes always so that the following is excluded: inhalation. skin contact. Eye contact. Take precautionary measures against static discharges.

Advice on protection against fire and explosion

Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well-ventilated place. Take precautionary measures against static discharges.

Hints on joint storage

Materials to avoid: Acid. Base. Material, combustible. Oxidizing agents.

Further information on storage conditions

Keep away from sources of ignition - No smoking. Protect against: heat. Keep/Store only in original container.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

**Safety Data Sheet**

according to UK REACH Regulation

WS-Plast® Dickschicht M 4200

Revision date: 13.03.2025

Product code: 1000

Page 5 of 12

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
123-42-2	4-Hydroxy-4-methyl-pentan-2-one	50	241		TWA (8 h)	WEL
		75	362		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
141-32-2	n-Butyl acrylate	1	5		TWA (8 h)	WEL
		5	26		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls**Appropriate engineering controls**

Occupational exposure controls: Refer to chapter 7. No further action is necessary.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Framed glasses. Goggles.

Hand protection

Tested protective gloves are to be worn:

Suitable material: NBR (Nitrile rubber), Butyl rubber.

Thickness of glove material: >0,4mm

penetration time (maximum wearing period): >480min

DIN-/EN-Norms EN ISO 374

Skin protection

Suitable protective clothing: Lab apron.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation . insufficient absorption.

Environmental exposure controls

Refer to chapter 7 No further action is necessary.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	characteristic
Odour:	characteristic

**Safety Data Sheet**

according to UK REACH Regulation

WS-Plast® Dickschicht M 4200

Revision date: 13.03.2025

Product code: 1000

Page 6 of 12

Odour threshold: not determined

	Test method
Boiling point or initial boiling point and boiling range:	122 °C DIN 51751
Lower explosion limits:	1,1 vol. %
Upper explosion limits:	7,0 vol. %
Flash point:	24 °C DIN 51376
Auto-ignition temperature:	270 °C DIN 53217
Vapour pressure:	7 hPa
(at 20 °C)	
Density (at 20 °C):	1,360 g/cm³ DIN 53217

9.2. Other information**Other safety characteristics**

Solvent separation test:	< 3%
Solvent content:	VOCV (CH): 32,1 %
	VOC (EU) 443,7 g/l
	67,9 %
Solid content:	
Softening point:	DIN 52025
Viscosity / dynamic:	10000 mPa·s
(at 20 °C)	
Flow time:	>30s 6 DIN EN ISO 2431
(at 20 °C)	

SECTION 10: Stability and reactivity**10.1. Reactivity**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.2. Chemical stability

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.3. Possibility of hazardous reactions

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.4. Conditions to avoid

Conditions to avoid:

In case of warming: Danger of bursting container.

10.5. Incompatible materials

Alkalis (alkalis). Acid. Oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Toxicological data are not available.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 5000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

**Safety Data Sheet**

according to UK REACH Regulation

WS-Plast® Dickschicht M 4200

Revision date: 13.03.2025

Product code: 1000

Page 7 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 8532 mg/kg	Rat	RTECS	
	dermal	LD50 7500 mg/kg	Rabbit		
64742-95-6	Lösungsmittelnaphtha, leichte aromatische, Benzolgehalt <0,1%				
	oral	LD50 2000 mg/kg	Rat		
	dermal	LD50 3160 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 5,2 mg/l	Rat		
100-41-4	ethylbenzene				
	oral	LD50 3500 mg/kg	Rat	GESTIS	
	dermal	LD50 15400 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 17,2 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol				
	oral	LD50 2520 mg/kg	Rat		
	dermal	LD50 13630 mg/kg	Rabbit		
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether				
	oral	LD50 > 5000 mg/kg	Rat	IUCLID	
	dermal	LD50 11000 mg/kg	Rabbit		

Irritation and corrosivity

Evaluation: non-irritant.

STOT-repeated exposure

Has de-greasing effect on the skin.

Specific effects in experiment on an animal

Rat LD50: 4300 - 5800 mg/kg Acute toxicity, oral

Data apply to the main component.

11.2. Information on other hazards**Further information**

Toxicological data are not available.

SECTION 12: Ecological information**12.1. Toxicity**

Doesn't get into the sewage water as long as the process is carried out according to regulations.

**Safety Data Sheet**

according to UK REACH Regulation

WS-Plast® Dickschicht M 4200

Revision date: 13.03.2025

Product code: 1000

Page 8 of 12

Very toxic for Water fleas.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50 161 mg/l	96 h	Pimephales promelas		
	Acute crustacea toxicity	EC50 408 mg/l	48 h	Daphnia magna		
100-41-4	ethylbenzene					
	Acute fish toxicity	LC50 4,2 mg/l	96 h	Oncorhynchus mykiss	ECHA	
	Acute algae toxicity	ErC50 3,6 mg/l	96 h	Algen	GESTIS	
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol					
	Acute fish toxicity	LC50 420 mg/l	96 h	Lepomis macrochirus		
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether					
	Acute fish toxicity	LC50 4600 - 10000 mg/l	96 h	Leuciscus idus	IUCLID	
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 > 500 mg/l	48 h	Daphnia magna	IUCLID	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-65-6	2-methoxy-1-methylethyl acetate	0,43
100-41-4	ethylbenzene	3,15
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol	1,03
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	-0,437

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

No data available

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

List of Wastes Code - residues/unused products

**Safety Data Sheet**

according to UK REACH Regulation

WS-Plast® Dickschicht M 4200

Revision date: 13.03.2025

Product code: 1000

Page 9 of 12

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Hand over to officially registered waste disposal company.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: PAINT
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 163 367 650
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Other applicable information (land transport)

If this product is transported in containers of a maximum capacity of 450 l according to ADR/RID No. 2.2.3.1.5., it is not referred to as a dangerous good in terms of transport regulations.

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 163 367 650
Limited quantity: 5 L
Excepted quantity: E1

**Safety Data Sheet**

according to UK REACH Regulation

WS-Plast® Dickschicht M 4200

Revision date: 13.03.2025

Product code: 1000

Page 10 of 12

Other applicable information (inland waterways transport)

If this product is transported in containers of a maximum capacity of 450 l according to ADR/RID No. 2.2.3.1.5., it is not referred to as a dangerous good in terms of transport regulations.

Marine transport (IMDG)**14.1. UN number or ID number:** UN 1263**14.2. UN proper shipping name:** PAINT**14.3. Transport hazard class(es):** 3**14.4. Packing group:** III

Hazard label: 3



Special Provisions: 163, 223, 367, 955

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-E, S-E

Other applicable information (marine transport)

Transport in accordance with paragraph 2.3.2.5 of the IMDG Code.

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:** UN 1263**14.2. UN proper shipping name:** PAINT**14.3. Transport hazard class(es):** 3**14.4. Packing group:** III

Hazard label: 3



Special Provisions: A3 A72 A192

Limited quantity Passenger: 10 L

Passenger LQ: Y344

Excepted quantity: E1

IATA-packing instructions - Passenger: 355

IATA-max. quantity - Passenger: 60 L

IATA-packing instructions - Cargo: 366

IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in
paints and varnishes: VOCV (CH): 32,1 %
VOC (EU) 443,7 g/l

**Safety Data Sheet**

according to UK REACH Regulation

WS-Plast® Dickschicht M 4200

Revision date: 13.03.2025

Product code: 1000

Page 11 of 12

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Abbreviations and acronyms**

Flam. Liq: Flammable liquids
Acute Tox: Acute toxicity
Asp. Tox: Aspiration hazard
Skin Irrit: Skin irritation
Eye Irrit: Eye irritation
Skin Sens: Skin sensitisation
Carc: Carcinogenicity
STOT SE: Specific target organ toxicity - single exposure
STOT RE: Specific target organ toxicity - repeated exposure
Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	
STOT RE 2; H373	
Aquatic Chronic 3; H412	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains n-butyl acrylate. May produce an allergic reaction.
EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Further Information

The product is classified and labelled according to EC directives or corresponding national laws.

The above information describes exclusively the safety requirements of the product and is based on our



Safety Data Sheet

according to UK REACH Regulation

WS-Plast® Dickschicht M 4200

Revision date: 13.03.2025

Product code: 1000

Page 12 of 12

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)