

Safety Data Sheet

according to UK REACH Regulation

WS Patina, verschiedenfarbig

Revision date: 13.03.2025 Product code: 14 Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

WS Patina, verschiedenfarbig

UFI: HSH0-1DEW-20DK-9NU3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Paint, Varnish. industrial paint

Uses advised against

Do not use for products which come into contact with the food stuffs.

1.3. Details of the supplier of the safety data sheet

Company name: W+S GmbH Lackchemie und Aerosol-Technik

Street: Am Sportplatz 5

Place: D-63791 Karlstein-Dettingen

Telephone: +49 6188 9575-0 Telefax: +49 6188 9575-30

E-mail: info@ws-lackchemie.de
Contact person: Abt. Produkt / Sicherheit
Responsible Department: Abt. Produkt / Sicherheit

1.4. Emergency telephone +49 551-19240 GIZ-Nord Poisons Centre

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

Hazard categories:

Flammable liquids: Flam. Liq. 3

Hazard Statements:

Flammable liquid and vapour.

2.2. Label elements

GB CLP Regulation

Signal word: Warning

Pictograms:



Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P271 Use only outdoors or in a well-ventilated area.

P501 Offer surplus and non-recyclable solutions to a licensed disposal company.
P370+P378 In case of fire: Use sand, dry chemical or alcohol-resistant foam to extinguish.

Special labelling of certain mixtures

EUH208 Contains methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate.

May produce an allergic reaction.

SECTION 3: Composition/information on ingredients



according to UK REACH Regulation

WS Patina, verschiedenfarbig

Revision date: 13.03.2025 Product code: 14 Page 2 of 13

3.2. Mixtures

Chemical characterization

Paint, Varnish.

Relevant ingredients

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification (GB CLP Regulation)				
64742-95-6	Lösungsmittelnaphta, leichte aroma	atische, Benzolgehalt <0,1%		15 - < 20 %	
	918-668-5		01-2119455851-35		
	Flam. Liq. 3, STOT SE 3, STOT SE H411 EUH066	3, Asp. Tox. 1, Aquatic Chronic 2; H	1226 H335 H336 H304		
1330-20-7	xylene			5 - < 10 %	
	215-535-7	601-022-00-9			
	Flam. Liq. 3, Acute Tox. 4, Acute To	ox. 4, Skin Irrit. 2; H226 H332 H312 F			
100-41-4	ethylbenzene			1 - < 5 %	
	202-849-4	601-023-00-4			
	Flam. Liq. 2, Acute Tox. 4, STOT R	E 2, Asp. Tox. 1; H225 H332 H373 H	1304		
123-42-2	4-hydroxy-4-methylpentan-2-one; c		1 - < 5 %		
	204-626-7	603-016-00-1			
	Eye Irrit. 2; H319				
108-65-6	2-methoxy-1-methylethyl acetate		1 - < 5 %		
	203-603-9	607-195-00-7			
	Flam. Liq. 3; H226	•			
1569-01-3	1-Propoxy-2-propanol		1 - < 5 %		
	216-372-4		01-2119474443-37		
	Flam. Liq. 3, Eye Irrit. 2; H226 H31	•			
107-98-2	1-methoxy-2-propanol; monopropy		1 - < 5 %		
	203-539-1	603-064-00-3			
	Flam. Liq. 3, STOT SE 3; H226 H3				
80-62-6	methyl methacrylate; methyl 2-metl	openoate	< 1 %		
	201-297-1	607-035-00-6			
	Flam. Liq. 2, Skin Irrit. 2, Skin Sens	1335			
63449-41-2	quaternary ammonium compounds	es	< 1 %		
	264-151-6	612-140-00-5			
	Acute Tox. 4, Acute Tox. 4, Skin Co				

Full text of H and EUH statements: see section 16.





according to UK REACH Regulation

WS Patina, verschiedenfarbig

Revision date: 13.03.2025 Product code: 14 Page 3 of 13

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity		
	Specific Conc				
64742-95-6	918-668-5	3-5 Lösungsmittelnaphta, leichte aromatische, Benzolgehalt <0,1%			
	inhalation: LC	C50 = 5,2 mg/l (vapours); dermal: LD50 = 3160 mg/kg; oral: LD50 = 2000 mg/kg			
1330-20-7	215-535-7	xylene	5 - < 10 %		
	inhalation: AT 1100 mg/kg				
100-41-4	202-849-4	ethylbenzene	1 - < 5 %		
	inhalation: LC LD50 = 15400				
123-42-2	204-626-7	4-hydroxy-4-methylpentan-2-one; diacetone alcohol	1 - < 5 %		
	dermal: LD50				
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	1 - < 5 %		
	dermal: LD50				
1569-01-3	216-372-4	1-Propoxy-2-propanol	1 - < 5 %		
	dermal: LD50				
107-98-2	203-539-1	1-methoxy-2-propanol; monopropylene glycol methyl ether	1 - < 5 %		
	dermal: LD50 = 11000 mg/kg; oral: LD50 = > 5000 mg/kg				
63449-41-2	264-151-6	quaternary ammonium compounds, benzyl-C8-18-alkyldimethyl, chlorides	< 1 %		
	dermal: ATE	= 1100 mg/kg; oral: ATE = 500 mg/kg			

Further Information

Full text of R-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Give nothing to eat or drink.

After inhalation

In case of inhaling spray mists, consult a doctor immediately and show him box or label. If victim is at risk of losing consciousness, position and transport on their side. Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water. Remove contaminated, saturated clothing immediately. Change contaminated clothing. Wash thoroughly the body (shower or bath).

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

If swallowed, immediately drink: Water. Do NOT induce vomiting. Call a physician immediately. Caution if victim vomits: Risk of aspiration!

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media



W+S GmbH Lackchemie und Aerosol-Technik

according to UK REACH Regulation

WS Patina, verschiedenfarbig

Revision date: 13.03.2025 Product code: 14 Page 4 of 13

Suitable extinguishing media

Carbon dioxide (CO2). Foam. Extinguishing powder. Dry extinguishing powder. Sand.

Unsuitable extinguishing media

Water. High power water jet.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Burning produces heavy smoke. In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately. Do not allow to enter into surface water or drains. Remove product from area of fire. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Provide adequate ventilation. Remove all sources of ignition. Provide adequate ventilation. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard. Do not allow to enter into surface water or drains. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Preventive measures: If handled uncovered, arrangements with local exhaust ventilation have to be used. It is recommended to design all work processes always so that the following is excluded: inhalation. skin contact. Eye contact. Take precautionary measures against static discharges.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep only in the original container in a cool, well-ventilated place. Take precautionary measures against static discharges.



W+S GmbH Lackchemie und Aerosol-Technik

according to UK REACH Regulation

WS Patina, verschiedenfarbig

Revision date: 13.03.2025 Product code: 14 Page 5 of 13

Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing. Materials to avoid: Acid. Base. Material, combustible. Oxidizing agents.

Further information on storage conditions

Keep away from sources of ignition - No smoking. Protect against: heat. Keep/Store only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
123-42-2	4-Hydroxy-4-methyl-pentan-2-one	50	241		TWA (8 h)	WEL
		75	362		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
80-62-6	Methyl methacrylate	50	208		TWA (8 h)	WEL
		100	416		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol		Post shift

8.2. Exposure controls

Appropriate engineering controls

Occupational exposure controls: Refer to chapter 7. No further action is necessary.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: Framed glasses. Goggles.

Hand protection

Tested protective gloves are to be worn:

Suitable material: NBR (Nitrile rubber)., Butyl rubber.

Thickness of glove material: >0,4mm

penetration time (maximum wearing period): >480min

DIN-/EN-Norms EN ISO 374

Skin protection

Suitable protective clothing: Lab apron.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation. insufficient absorbtion.



according to UK REACH Regulation

WS Patina, verschiedenfarbig

Revision date: 13.03.2025 Product code: 14 Page 6 of 13

Environmental exposure controls

Refer to chapter 7 No further action is necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: characteristic

Odour: hydrocarbons, aromatic.

Odour threshold: not determined

Test method

Boiling point or initial boiling point and 135 °C

boiling range:

Lower explosion limits:0,8 vol. %Upper explosion limits:8,2 vol. %Flash point:30 °CAuto-ignition temperature:315 °C

Water solubility: The study does not need to be conducted

because the substance is known to be

insoluble in water.

W+S GmbH Lackchemie und Aerosol-Technik

Vapour pressure: 7 hPa

(at 20 °C)

Density (at 20 °C): 1,04 g/cm³

9.2. Other information

Other safety characteristics

Solvent content: VOCV (CH): 47,36 %

VOC (EU): 443,641 g/l

Solid content: 51 %

Softening point: DIN 52025 Flow time: >600 s 3 DIN 53211

SECTION 10: Stability and reactivity

10.1. Reactivity

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.2. Chemical stability

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.3. Possibility of hazardous reactions

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard. Conditions to avoid:

In case of warming: Danger of bursting container.

10.5. Incompatible materials

Alkalis (alkalis). Acid. Oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation



W+S GmbH Lackchemie und Aerosol-Technik

according to UK REACH Regulation

WS Patina, verschiedenfarbig

Revision date: 13.03.2025 Product code: 14 Page 7 of 13

Acute toxicity

Toxicological data are not available.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l



according to UK REACH Regulation

WS Patina, verschiedenfarbig

Revision date: 13.03.2025 Product code: 14 Page 8 of 13

CAS No	Chemical name						
	Exposure route	Dose		Species	Source	Method	
64742-95-6	Lösungsmittelnaphta, leichte aromatische, Benzolgehalt <0,1%						
	oral	LD50 mg/kg	2000	Rat			
	dermal	LD50 mg/kg	3160	Rabbit.			
	inhalation (4 h) vapour	LC50	5,2 mg/l	Rat			
1330-20-7	xylene						
	dermal	ATE mg/kg	1100				
	inhalation vapour	ATE	11 mg/l				
	inhalation dust/mist	ATE	1,5 mg/l				
100-41-4	ethylbenzene						
	oral	LD50 mg/kg	3500	Rat	GESTIS		
	dermal	LD50 mg/kg	15400	Rabbit	GESTIS		
	inhalation (4 h) vapour	LC50	17,2 mg/l	Rat			
	inhalation dust/mist	ATE	1,5 mg/l				
123-42-2	4-hydroxy-4-methylpenta	n-2-one; dia	acetone alcoh	nol			
	oral	LD50 mg/kg	2520	Rat			
	dermal	LD50 mg/kg	13630	Rabbit			
108-65-6	2-methoxy-1-methylethyl acetate						
	oral	LD50 mg/kg	8532	Rat	RTECS		
	dermal	LD50 mg/kg	7500	Rabbit			
1569-01-3	1-Propoxy-2-propanol						
	oral	LD50 mg/kg	2504	Rat			
	dermal	LD50 mg/kg	3550	Rabbit			
107-98-2	1-methoxy-2-propanol; m		ne glycol met	thyl ether			
	oral	LD50 mg/kg	> 5000	Rat	IUCLID		
	dermal	LD50 mg/kg	11000	Rabbit			
63449-41-2	quaternary ammonium co		benzyl-C8-18	-alkyldimethyl, chloride	es		
	oral	ATE mg/kg	500				
	dermal	ATE mg/kg	1100				

Irritation and corrosivity

Evaluation: non-irritant.

STOT-repeated exposure

Has de-greasing effect on the skin.





according to UK REACH Regulation

WS Patina, verschiedenfarbig

Revision date: 13.03.2025 Product code: 14 Page 9 of 13

Specific effects in experiment on an animal

Rat LD50: 4300 - 5800 mg/kg Acute toxicity, oral

Data apply to the main component.

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

11.2. Information on other hazards

Further information

Toxicological data are not available.

SECTION 12: Ecological information

12.1. Toxicity

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Doesn't get into the sewage water as long as the process is carried out according to regulations.

Very toxic for Water fleas.

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
100-41-4	ethylbenzene						
	Acute fish toxicity	LC50	4,2 mg/l	96 h	Oncorhynchus mykiss	ECHA	
	Acute algae toxicity	ErC50	3,6 mg/l	96 h	Algen	GESTIS	
123-42-2	4-hydroxy-4-methylpentar	n-2-one; diace	etone alcoh	ol			
	Acute fish toxicity	LC50	420 mg/l	96 h	Lepomis macrochirus		
108-65-6	2-methoxy-1-methylethyl acetate						
	Acute fish toxicity	LC50	161 mg/l	96 h	Pimephales promelas		
	Acute crustacea toxicity	EC50	408 mg/l	48 h	Daphnia magna		
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether						
	Acute fish toxicity	LC50 10000 mg/l	4600 -	96 h	Leuciscus idus	IUCLID	
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 mg/l	> 500	48 h	Daphnia magna	IUCLID	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
100-41-4	ethylbenzene	3,15
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol	1,03
108-65-6	2-methoxy-1-methylethyl acetate	0,43
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	-0,437

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH. No data available



Safety Data Sheet

according to UK REACH Regulation

WS Patina, verschiedenfarbig

Revision date: 13.03.2025 Product code: 14 Page 10 of 13

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF

COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish

containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Hand over to officially registered waste disposal company.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:UN 126314.2. UN proper shipping name:PAINT14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1

Special Provisions: 163 367 650

Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E





according to UK REACH Regulation

WS Patina, verschiedenfarbig

Revision date: 13.03.2025 Product code: 14 Page 11 of 13

Other applicable information (land transport)

If this product is transportet in containers of a maximum capacity of 450 I according to ADR/RID No. 2.2.3.1.5., it is not referred to as a dangerous good in terms of transport regulations.

Inland waterways transport (ADN)

14.1. UN number or ID number:UN 126314.2. UN proper shipping name:Paint14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1

Special Provisions: 163 367 650

Limited quantity: 5 L
Excepted quantity: E1

Other applicable information (inland waterways transport)

If this product is transportet in containers of a maximum capacity of 450 I according to ADR/RID No. 2.2.3.1.5., it is not referred to as a dangerous good in terms of transport regulations.

Marine transport (IMDG)

14.1. UN number or ID number:UN 126314.2. UN proper shipping name:PAINT14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Special Provisions: 163, 223, 367, 955

Other applicable information (marine transport)

Transport in accordance with paragraph 2.3.2.5 of the IMDG Code.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:UN 126314.2. UN proper shipping name:PAINT14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Special Provisions: A3 A72 A192

Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1

IATA-packing instructions - Passenger:355IATA-max. quantity - Passenger:60 LIATA-packing instructions - Cargo:366IATA-max. quantity - Cargo:220 L



Safety Data Sheet

according to UK REACH Regulation

WS Patina, verschiedenfarbig

Revision date: 13.03.2025 Product code: 14 Page 12 of 13

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII): Entry 3, Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in VOCV (CH): 47,36 % paints and varnishes: VOC (EU): 443,641 g/l

National regulatory information

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

Abbreviations and acronyms

Flam. Liq: Flammable liquids Acute Tox: Acute toxicity Asp. Tox: Aspiration hazard Skin Corr: Skin corrosion Skin Irrit: Skin irritation Eye Irrit: Eye irritation Skin Sens: Skin sensitisation

STOT SE: Specific target organ toxicity - single exposure STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard Aquatic Chronic: Chronic aquatic hazard

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.



Safety Data Sheet

according to UK REACH Regulation

WS Patina, verschiedenfarbig

Revision date: 13.03.2025 Product code: 14 Page 13 of 13

EUH208

Contains methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate. May produce an allergic reaction.

Further Information

The product is classified and labelled according to EC directives or corresponding national laws.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)