

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Plast® Verdünnung MV 751**

Revision date: 13.03.2025

Product code: 4001

Page 1 of 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

WS-Plast® Verdünnung MV 751

UFI: JXW5-V922-6VJJ-KV3T

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

Solvent/Thinner.

**Uses advised against**

Do not use for products which come into contact with the food stuffs.

**1.3. Details of the supplier of the safety data sheet**

Company name: W+S GmbH Lackchemie und Aerosol-Technik

Street: Am Sportplatz 5

Place: D-63791 Karlstein-Dettingen

Telephone: +49 6188 9575-0

Telefax: +49 6188 9575-30

E-mail: info@ws-lackchemie.de

Contact person: Abt. Produkt / Sicherheit

Responsible Department: Abt. Produkt / Sicherheit

**1.4. Emergency telephone number:** +49 551-19240 GIZ-Nord Poisons Centre**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard Statements:

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

**2.2. Label elements****GB CLP Regulation****Hazard components for labelling**

Lösungsmittelnaphtha, leichte aromatische, Benzolgehalt &lt;0,1%

Signal word: Danger

Pictograms:

**Hazard statements**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Plast® Verdünnung MV 751**

Revision date: 13.03.2025

Product code: 4001

Page 2 of 9

P273 Avoid release to the environment.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P331 Do NOT induce vomiting.  
P403+P235 Store in a well-ventilated place. Keep cool.

**Special labelling of certain mixtures**

EUH066 Repeated exposure may cause skin dryness or cracking.

**SECTION 3: Composition/information on ingredients****3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-95-6	Lösungsmittelnaphtha, leichte aromatische, Benzolgehalt <0,1%			80 - < 85 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H336 H304 H411 EUH066			
108-65-6	2-methoxy-1-methylethyl acetate			15 - < 20 %
	203-603-9	607-195-00-7		
	Flam. Liq. 3; H226			
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol			1 - < 5 %
	204-626-7	603-016-00-1		
	Eye Irrit. 2; H319			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
64742-95-6	918-668-5	Lösungsmittelnaphtha, leichte aromatische, Benzolgehalt <0,1%	80 - < 85 %
	inhalation: LC50 = 5,2 mg/l (vapours); dermal: LD50 = 3160 mg/kg; oral: LD50 = 2000 mg/kg		
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	15 - < 20 %
	dermal: LD50 = 7500 mg/kg; oral: LD50 = 8532 mg/kg		
123-42-2	204-626-7	4-hydroxy-4-methylpentan-2-one; diacetone alcohol	1 - < 5 %
	dermal: LD50 = 13630 mg/kg; oral: LD50 = 2520 mg/kg Eye Irrit. 2; H319: >= 10 - 100		

**Further Information**

Full text of R-phrases: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Give nothing to eat or drink.

**After inhalation**

In case of inhaling spray mists, consult a doctor immediately and show him box or label. If victim is at risk of losing consciousness, position and transport on their side. Provide fresh air.

**After contact with skin**

Remove contaminated, saturated clothing immediately. Change contaminated clothing. Wash thoroughly the body (shower or bath).

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Plast® Verdünnung MV 751**

Revision date: 13.03.2025

Product code: 4001

Page 3 of 9

**After contact with eyes**

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

**After ingestion**

Do NOT induce vomiting. Call a physician immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

Frequently or prolonged contact with skin may cause dermal irritation.

**4.3. Indication of any immediate medical attention and special treatment needed**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

Foam. Dry extinguishing powder. Carbon dioxide (CO<sub>2</sub>). ABC powder.

**Unsuitable extinguishing media**

High power water jet.

**5.2. Special hazards arising from the substance or mixture**

Burning produces heavy smoke. In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. See protective measures under point 7 and 8.

**6.3. Methods and material for containment and cleaning up****Other information**

Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

See protective measures under point 7 and 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Preventive measures: If handled uncovered, arrangements with local exhaust ventilation have to be used. It is recommended to design all work processes always so that the following is excluded: inhalation. skin contact. Eye contact. Take precautionary measures against static discharges.

**Advice on protection against fire and explosion**

Vapours may form explosive mixtures with air.

**Advice on general occupational hygiene**

Observe the wear time limits according to GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep only in the original container in a cool, well-ventilated place. Take precautionary measures against static discharges.

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Plast® Verdünnung MV 751**

Revision date: 13.03.2025

Product code: 4001

Page 4 of 9

**Hints on joint storage**

Materials to avoid: Acid. Base. Material, combustible. Oxidizing agents.

**Further information on storage conditions**

Keep away from sources of ignition - No smoking. Protect against: heat. Keep/Store only in original container.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
123-42-2	4-Hydroxy-4-methyl-pentan-2-one	50	241		TWA (8 h)	WEL
		75	362		STEL (15 min)	WEL

**8.2. Exposure controls****Appropriate engineering controls**

Occupational exposure controls: Refer to chapter 7. No further action is necessary.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Suitable eye protection: Framed glasses. Goggles.

**Hand protection**

Tested protective gloves are to be worn:

Suitable material: NBR (Nitrile rubber), Butyl rubber.

Thickness of glove material: &gt;0,4mm

penetration time (maximum wearing period): &gt;480min

DIN-/EN-Norms EN ISO 374

**Skin protection**

Suitable protective clothing: Lab apron.

**Respiratory protection**

Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation . insufficient absorption.

**Environmental exposure controls**

Refer to chapter 7 No further action is necessary.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	colourless
Odour:	characteristic
Odour threshold:	not determined
Boiling point or initial boiling point and boiling range:	135 °C
Lower explosion limits:	0,8 vol. %
Upper explosion limits:	10,8 vol. %
Flash point:	40 °C
Auto-ignition temperature:	315 °C
Vapour pressure:	3,1 hPa
(at 20 °C)	

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Plast® Verdünnung MV 751**

Revision date: 13.03.2025

Product code: 4001

Page 5 of 9

Density (at 20 °C):

0,886 g/cm<sup>3</sup>**9.2. Other information****Other safety characteristics**

Solvent content:

100 %

VOC value 886

Solid content:

0 %

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

**10.2. Chemical stability**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

**10.3. Possibility of hazardous reactions**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

**10.4. Conditions to avoid**

Conditions to avoid:

In case of warming: Danger of bursting container.

**10.5. Incompatible materials**

Alkalis (alkalis). Acid. Oxidizing agents.

**10.6. Hazardous decomposition products**

Thermal decomposition can lead to the escape of irritating gases and vapors.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Toxicological data are not available.

**ATEmix calculated**

ATE (oral) &gt; 2000 mg/kg; ATE (dermal) &gt; 2000 mg/kg; ATE (inhalation vapour) &gt; 20 mg/l; ATE (inhalation dust/mist) &gt; 5 mg/l

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
64742-95-6	Lösungsmittelnaphtha, leichte aromatische, Benzolgehalt <0,1%					
	oral	LD50 mg/kg	2000	Rat		
	dermal	LD50 mg/kg	3160	Rabbit		
	inhalation (4 h) vapour	LC50	5,2 mg/l	Rat		
108-65-6	2-methoxy-1-methylethyl acetate					
	oral	LD50 mg/kg	8532	Rat	RTECS	
	dermal	LD50 mg/kg	7500	Rabbit		
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol					
	oral	LD50 mg/kg	2520	Rat		
	dermal	LD50 mg/kg	13630	Rabbit		

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Plast® Verdünnung MV 751**

Revision date: 13.03.2025

Product code: 4001

Page 6 of 9

**Irritation and corrosivity**

Frequently or prolonged contact with skin may cause dermal irritation.

**STOT-repeated exposure**

Has de-greasing effect on the skin.

**Specific effects in experiment on an animal**

Rat LD50: 4300 - 5800 mg/kg Acute toxicity, oral

Data apply to the main component.

**11.2. Information on other hazards****Further information**

Toxicological data are not available.

**SECTION 12: Ecological information****12.1. Toxicity**

Doesn't get into the sewage water as long as the process is carried out according to regulations.

Very toxic for Water fleas.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h]   [d]	Species	Source	Method
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50	161 mg/l	96 h	Pimephales promelas	
	Acute crustacea toxicity	EC50	408 mg/l	48 h	Daphnia magna	
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol					
	Acute fish toxicity	LC50	420 mg/l	96 h	Lepomis macrochirus	

**12.2. Persistence and degradability**

No data available

**12.3. Bioaccumulative potential**

No data available

**Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
108-65-6	2-methoxy-1-methylethyl acetate	0,43
123-42-2	4-hydroxy-4-methylpentan-2-one; diacetone alcohol	1,03

**12.4. Mobility in soil**

No data available

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

No data available

**12.6. Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

**12.7. Other adverse effects**

No data available

**Further information**

Do not allow uncontrolled leakage of product into the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Plast® Verdünnung MV 751**

Revision date: 13.03.2025

Product code: 4001

Page 7 of 9

**List of Wastes Code - residues/unused products**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - used product**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**List of Wastes Code - contaminated packaging**

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

**Contaminated packaging**

Hand over to officially registered waste disposal company.

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number or ID number:** UN 1263  
**14.2. UN proper shipping name:** PAINT RELATED MATERIAL  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Special Provisions: 163 367 650  
Limited quantity: 5 L  
Excepted quantity: E1  
Transport category: 3  
Hazard No: 30  
Tunnel restriction code: D/E

**Inland waterways transport (ADN)**

**14.1. UN number or ID number:** UN 1263  
**14.2. UN proper shipping name:** Paint related material  
**14.3. Transport hazard class(es):** 3  
**14.4. Packing group:** III  
Hazard label: 3



Classification code: F1  
Special Provisions: 163 367 650  
Limited quantity: 5 L  
Excepted quantity: E1

**Marine transport (IMDG)**

**14.1. UN number or ID number:** UN 1263  
**14.2. UN proper shipping name:** PAINT RELATED MATERIAL

**Safety Data Sheet**

according to UK REACH Regulation

**WS-Plast® Verdünnung MV 751**

Revision date: 13.03.2025

Product code: 4001

Page 8 of 9

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

III

Hazard label:

3



Special Provisions:

163, 223, 367, 955

Limited quantity:

5 L

Excepted quantity:

E1

EmS:

F-E, S-E

**Air transport (ICAO-TI/IATA-DGR)****14.1. UN number or ID number:**

UN 1263

**14.2. UN proper shipping name:**

PAINT RELATED MATERIAL

**14.3. Transport hazard class(es):**

3

**14.4. Packing group:**

III

Hazard label:

3



Special Provisions:

A3 A72 A192

Limited quantity Passenger:

10 L

Passenger LQ:

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger:

355

IATA-max. quantity - Passenger:

60 L

IATA-packing instructions - Cargo:

366

IATA-max. quantity - Cargo:

220 L

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS:

Yes



Danger releasing substance:

Lösungsmittelnaphta, leichte aromatische, Benzolgehalt &lt;0,1%

**14.6. Special precautions for user**

No information available.

**14.7. Maritime transport in bulk according to IMO instruments**

No information available.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in  
paints and varnishes:

100 %

VOC value 886

**National regulatory information**

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.



**Safety Data Sheet**

according to UK REACH Regulation

**WS-Plast® Verdünnung MV 751**

Revision date: 13.03.2025

Product code: 4001

Page 9 of 9

Water hazard class (D):

2 - obviously hazardous to water

**15.2. Chemical safety assessment**

For this substance a chemical safety assessment has not been carried out.

**SECTION 16: Other information****Abbreviations and acronyms**

Flam. Liq: Flammable liquids

Asp. Tox: Aspiration hazard

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

**Relevant H and EUH statements (number and full text)**

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

**Further Information**

The product is classified and labelled according to EC directives or corresponding national laws.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*