

**Safety Data Sheet**

according to UK REACH Regulation

WS-Haftgrund M 4021

Revision date: 13.03.2025

Product code: 5001

Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

WS-Haftgrund M 4021

UFI: 2JX5-D9VU-CVJ1-7868

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**Paint, Varnish.
industrial paint**Uses advised against**

Do not use for products which come into contact with the food stuffs.

1.3. Details of the supplier of the safety data sheet

Company name:	W+S GmbH Lackchemie und Aerosol-Technik	
Street:	Am Sportplatz 5	
Place:	D-63791 Karlstein-Dettingen	
Telephone:	+49 6188 9575-0	Telefax: +49 6188 9575-30
E-mail:	info@ws-lackchemie.de	
Contact person:	Abt. Produkt / Sicherheit	
Responsible Department:	Abt. Produkt / Sicherheit	

1.4. Emergency telephone number: +49 551-19240 GIZ-Nord Poisons Centre**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**Flam. Liq. 3; H226
Skin Irrit. 2; H315
Eye Irrit. 2; H319
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**xylene
ethylbenzene
Quarz (Siliciumdioxid)**Signal word:** Warning**Pictograms:****Hazard statements**

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

**Safety Data Sheet**

according to UK REACH Regulation

WS-Haftgrund M 4021

Revision date: 13.03.2025

Product code: 5001

Page 2 of 12

Precautionary statements

- P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P370+P378 In case of fire: Use sand, dry chemical or alcohol-resistant foam to extinguish.
P501 Offer surplus and non-recyclable solutions to a licensed disposal company.

Additional advice on labelling

The product is classified and labelled according to EC directives or corresponding national laws.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

Paint, Varnish.

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
1330-20-7	xylene			20 - < 25 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			
100-41-4	ethylbenzene			5 - < 10 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
7779-90-0	trizinc bis(orthophosphate)			5 - < 10 %
	231-944-3	030-011-00-6		
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
14808-60-7	Quarz (Siliciumdioxid)			5 - < 10 %
	238-878-4			
	Acute Tox. 4; H332			
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether			1 - < 5 %
	203-539-1	603-064-00-3		
	Flam. Liq. 3, STOT SE 3; H226 H336			
78-83-1	2-methylpropan-1-ol; iso-butanol			1 - < 5 %
	201-148-0	603-108-00-1		
	Flam. Liq. 3, Skin Irrit. 2, Eye Dam. 1, STOT SE 3, STOT SE 3; H226 H315 H318 H335 H336			
68308-64-5	Quaternäre Ammoniumverbindungen, Kokosalkylethylidimethyl-, Ethylsulfate			< 1 %
	269-662-8			
	Acute Tox. 4, Skin Irrit. 2, Eye Dam. 1, Aquatic Acute 1; H302 H315 H318 H400			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

WS-Haftgrund M 4021

Revision date: 13.03.2025

Product code: 5001

Page 3 of 12

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
1330-20-7	215-535-7	xylene	20 - < 25 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg	
100-41-4	202-849-4	ethylbenzene	5 - < 10 %
		inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg	
14808-60-7	238-878-4	Quarz (Siliciumdioxid)	5 - < 10 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists)	
107-98-2	203-539-1	1-methoxy-2-propanol; monopropylene glycol methyl ether	1 - < 5 %
		dermal: LD50 = 11000 mg/kg; oral: LD50 = > 5000 mg/kg	
78-83-1	201-148-0	2-methylpropan-1-ol; iso-butanol	1 - < 5 %
		inhalation: LC50 = > 24 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 2830 mg/kg	
68308-64-5	269-662-8	Quaternäre Ammoniumverbindungen, Kokosalkylethylidimethyl-, Ethylsulfate	< 1 %
		oral: ATE = 500 mg/kg	

Further Information

Full text of R-phrases: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Give nothing to eat or drink.

After inhalation

In case of inhaling spray mists, consult a doctor immediately and show him box or label. If victim is at risk of losing consciousness, position and transport on their side. Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water. Subsequently wash off with: Polyethylene glykol 400. Medical treatment necessary. Remove contaminated, saturated clothing immediately. Change contaminated clothing. Wash thoroughly the body (shower or bath).

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

If swallowed, immediately drink: Water. Do NOT induce vomiting. Call a physician immediately. Caution if victim vomits: Risk of aspiration!

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam. Dry extinguishing powder. Carbon dioxide (CO₂). ABC powder.

**Safety Data Sheet**

according to UK REACH Regulation

WS-Haftgrund M 4021

Revision date: 13.03.2025

Product code: 5001

Page 4 of 12

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Burning produces heavy smoke. In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Contaminated fire-fighting water must be collected separately. Remove product from area of fire. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Preventive measures: If handled uncovered, arrangements with local exhaust ventilation have to be used. It is recommended to design all work processes always so that the following is excluded: inhalation. skin contact. Eye contact. Take precautionary measures against static discharges.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep only in the original container in a cool, well-ventilated place. Take precautionary measures against static discharges.

Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing. Materials to avoid: Acid. Base. Material, combustible. Oxidizing agents.

**Safety Data Sheet**

according to UK REACH Regulation

WS-Haftgrund M 4021

Revision date: 13.03.2025

Product code: 5001

Page 5 of 12

Further information on storage conditions

Keep away from sources of ignition - No smoking. Protect against: heat. Keep/Store only in original container.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL
78-83-1	2-Methylpropan-1-ol	50	154		TWA (8 h)	WEL
		75	231		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls**Appropriate engineering controls**

Occupational exposure controls: Refer to chapter 7. No further action is necessary.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Framed glasses. Goggles.

Hand protection

Tested protective gloves are to be worn:

Suitable material: NBR (Nitrile rubber), Butyl rubber.

Thickness of glove material: >0,4mm

penetration time (maximum wearing period): >480min

DIN-/EN-Norms EN ISO 374

Skin protection

Suitable protective clothing: Lab apron.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation . insufficient absorption.

Environmental exposure controls

Refer to chapter 7 No further action is necessary.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	yellow
Odour:	characteristic
Odour threshold:	not determined

**Safety Data Sheet**

according to UK REACH Regulation

WS-Haftgrund M 4021

Revision date: 13.03.2025

Product code: 5001

Page 6 of 12

Test method

Boiling point or initial boiling point and boiling range:	120 °C
Lower explosion limits:	1 vol. %
Upper explosion limits:	8 vol. %
Flash point:	23 °C
Auto-ignition temperature:	325 °C
Vapour pressure:	10 hPa
(at 20 °C)	
Density:	1,385 g/cm ³ DIN 53217

9.2. Other information**Other safety characteristics**

Solvent content:	VOCV (CH): 32,066 %
	VOC (EU): 444,241 g/l
Solid content:	68 %
Flow time:	280 (3 mm) 3 DIN 53211
(at 20 °C)	

SECTION 10: Stability and reactivity**10.1. Reactivity**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.2. Chemical stability

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.3. Possibility of hazardous reactions

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard. Conditions to avoid:
In case of warming: Danger of bursting container.

10.5. Incompatible materials

Alkalis (alkalis). Acid. Oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Toxicological data are not available.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) 4,082 mg/l

**Safety Data Sheet**

according to UK REACH Regulation

WS-Haftgrund M 4021

Revision date: 13.03.2025

Product code: 5001

Page 7 of 12

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
100-41-4	ethylbenzene				
	oral	LD50 3500 mg/kg	Rat	GESTIS	
	dermal	LD50 15400 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 17,2 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
14808-60-7	Quarz (Siliciumdioxid)				
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether				
	oral	LD50 > 5000 mg/kg	Rat	IUCLID	
	dermal	LD50 11000 mg/kg	Rabbit		
78-83-1	2-methylpropan-1-ol; iso-butanol				
	oral	LD50 > 2830 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rat		
	inhalation (4 h) vapour	LC50 > 24 mg/l	Rat		
68308-64-5	Quaternäre Ammoniumverbindungen, Kokosalkylethyldimethyl-, Ethylsulfate				
	oral	ATE 500 mg/kg			

Irritation and corrosivity

Evaluation: non-irritant.

Sensitising effects

@1501.B015584

STOT-repeated exposure

Has de-greasing effect on the skin.

Specific effects in experiment on an animal

Rat LD50: 4300 - 5800 mg/kg Acute toxicity, oral

Data apply to the main component.

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

11.2. Information on other hazards**Further information**

Toxicological data are not available.

SECTION 12: Ecological information

**Safety Data Sheet**

according to UK REACH Regulation

WS-Haftgrund M 4021

Revision date: 13.03.2025

Product code: 5001

Page 8 of 12

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Doesn't get into the sewage water as long as the process is carried out according to regulations.

Very toxic for Water fleas.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
100-41-4	ethylbenzene					
	Acute fish toxicity	LC50 4,2 mg/l	96 h	Oncorhynchus mykiss	ECHA	
	Acute algae toxicity	ErC50 3,6 mg/l	96 h	Algen	GESTIS	
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether					
	Acute fish toxicity	LC50 4600 - 10000 mg/l	96 h	Leuciscus idus	IUCLID	
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 > 500 mg/l	48 h	Daphnia magna	IUCLID	
78-83-1	2-methylpropan-1-ol; iso-butanol					
	Acute fish toxicity	LC50 1430 mg/l	96 h	Pimephales promelas		
	Acute algae toxicity	ErC50 1250 mg/l		Desmodesmus subspicatus		
	Acute crustacea toxicity	EC50 1439 mg/l	48 h	Daphnia magna		

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
100-41-4	ethylbenzene	3,15
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	-0,437
78-83-1	2-methylpropan-1-ol; iso-butanol	0,79

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

No data available

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

**Safety Data Sheet**

according to UK REACH Regulation

WS-Haftgrund M 4021

Revision date: 13.03.2025

Product code: 5001

Page 9 of 12

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Hand over to officially registered waste disposal company.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN 1263

14.2. UN proper shipping name: PAINT

14.3. Transport hazard class(es): 3

14.4. Packing group: III

Hazard label: 3



Classification code: F1

Special Provisions: 163 367 650

Limited quantity: 5 L

Excepted quantity: E1

Transport category: 3

Hazard No: 30

Tunnel restriction code: D/E

Other applicable information (land transport)

: 163 640E 650

: 3

: E

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1263

14.2. UN proper shipping name: Paint

14.3. Transport hazard class(es): 3

14.4. Packing group: III

Hazard label: 3



**Safety Data Sheet**

according to UK REACH Regulation

WS-Haftgrund M 4021

Revision date: 13.03.2025

Product code: 5001

Page 10 of 12

Classification code: F1
Special Provisions: 163 367 650
Limited quantity: 5 L
Excepted quantity: E1

Other applicable information (inland waterways transport)
: 163 640E 650

Marine transport (IMDG)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: PAINT
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: 163, 223, 367, 955
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: PAINT
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Special Provisions: A3 A72 A192
Limited quantity Passenger: 10 L
Passenger LQ: Y344
Excepted quantity: E1
IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: trizinc bis(orthophosphate)

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

**Safety Data Sheet**

according to UK REACH Regulation

WS-Haftgrund M 4021

Revision date: 13.03.2025

Product code: 5001

Page 11 of 12

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

Directive 2004/42/EC on VOC in
paints and varnishes:

VOCV (CH): 32,066 %

VOC (EU): 444,241 g/l

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Abbreviations and acronyms**

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

Eye Dam: Eye damage

Eye Irrit: Eye irritation

STOT SE: Specific target organ toxicity - single exposure

STOT RE: Specific target organ toxicity - repeated exposure

Aquatic Acute: Acute aquatic hazard

Aquatic Chronic: Chronic aquatic hazard

Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Flam. Liq. 3; H226	On basis of test data
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Further Information

The product is classified and labelled according to EC directives or corresponding national laws.

The above information describes exclusively the safety requirements of the product and is based on our



Safety Data Sheet

according to UK REACH Regulation

WS-Haftgrund M 4021

Revision date: 13.03.2025

Product code: 5001

Page 12 of 12

present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)