

**Safety Data Sheet**

according to UK REACH Regulation

WS Alu-Kontakt-Farbe AK 7900

Revision date: 13.03.2025

Product code: 5790

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

WS Alu-Kontakt-Farbe AK 7900

UFI: WE06-J92K-2VJW-SS0P

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**industrial paint
Paint, Varnish.**Uses advised against**

Do not use for products which come into contact with the food stuffs.

1.3. Details of the supplier of the safety data sheet

Company name:	W+S GmbH Lackchemie und Aerosol-Technik	
Street:	Am Sportplatz 5	
Place:	D-63791 Karlstein-Dettingen	
Telephone:	+49 6188 9575-0	Telefax: +49 6188 9575-30
E-mail:	info@ws-lackchemie.de	
Contact person:	Abt. Produkt / Sicherheit	
Responsible Department:	Abt. Produkt / Sicherheit	

1.4. Emergency telephone number: +49 551-19240 GIZ-Nord Poisons Centre**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**Flam. Liq. 3; H226
Skin Irrit. 2; H315
Eye Irrit. 2; H319
STOT SE 3; H335
Aquatic Chronic 3; H412

Full text of hazard statements: see SECTION 16.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**xylene
ethylbenzene**Signal word:** Warning**Pictograms:****Hazard statements**

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H412	Harmful to aquatic life with long lasting effects.

**Safety Data Sheet**

according to UK REACH Regulation

WS Alu-Kontakt-Farbe AK 7900

Revision date: 13.03.2025

Product code: 5790

Page 2 of 11

Precautionary statements

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P261 Avoid breathing Gas/fumes/vapour/spray.
- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P302+P352 IF ON SKIN: Wash with plenty of water and soap.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER/doctor if you feel unwell.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
1330-20-7	xylene			30 - < 35 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			
7429-90-5	aluminium powder (stabilised)			15 - < 20 %
	231-072-3	013-002-00-1		
	Flam. Sol. 1, Water-react. 2; H228 H261			
100-41-4	ethylbenzene			5 - < 10 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
64742-48-9	Hydrocarbons, C9-C11, alkanes, aromatics < 2 %			5 - < 10 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304			
	Hydrocarbons Liquid, C10-C13,			5 - < 10 %
	918-481-9		01-2119457273-39	
	Flam. Liq. 4, Skin Irrit. 3, Asp. Tox. 1; H227 H316 H304 EUH066			
	Hydrocarbons, C9-C12, n-alkanes, cyclics, aromatics (<2%)			5 - < 10 %
	920-134-1		01-2119480153-44	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 3; H226 H336 H304 H412			

Full text of H and EUH statements: see section 16.

**Safety Data Sheet**

according to UK REACH Regulation

WS Alu-Kontakt-Farbe AK 7900

Revision date: 13.03.2025

Product code: 5790

Page 3 of 11

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
Specific Conc. Limits, M-factors and ATE			
1330-20-7	215-535-7	xylene	30 - < 35 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg	
100-41-4	202-849-4	ethylbenzene	5 - < 10 %
		inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg	
64742-48-9	919-857-5	Hydrocarbons, C9-C11, alkanes, aromatics < 2 %	5 - < 10 %
		dermal: LD50 = 2001 mg/kg; oral: LD50 = 5001 mg/kg	
	918-481-9	Hydrocarbons Liquid, C10-C13,	5 - < 10 %
		dermal: LD50 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
	920-134-1	Hydrocarbons, C9-C12, n-alkanes, cyclics, aromatics (<2%)	5 - < 10 %
		inhalation: LC50 = 5001 mg/l (vapours); dermal: LD50 = 5001 mg/kg; oral: LD50 = 15001 mg/kg	

Further Information

Full text of R-phrases: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Give nothing to eat or drink.

After inhalation

Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm. In case of inhaling spray mists, consult a doctor immediately and show him box or label. If victim is at risk of losing consciousness, position and transport on their side.

After contact with skin

After contact with skin, wash immediately with: Water. Medical treatment necessary. Remove contaminated, saturated clothing immediately. Change contaminated clothing. Wash thoroughly the body (shower or bath).

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

If swallowed, immediately drink: Water. Do NOT induce vomiting. Give nothing to eat or drink. Call a physician immediately.

Caution if victim vomits: Risk of aspiration!

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam. Dry extinguishing powder. Carbon dioxide (CO₂). ABC powder.

Unsuitable extinguishing media

High power water jet.

**Safety Data Sheet**

according to UK REACH Regulation

WS Alu-Kontakt-Farbe AK 7900

Revision date: 13.03.2025

Product code: 5790

Page 4 of 11

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Burning produces heavy smoke. In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Preventive measures: If handled uncovered, arrangements with local exhaust ventilation have to be used. It is recommended to design all work processes always so that the following is excluded: inhalation. skin contact. Eye contact. Take precautionary measures against static discharges.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Keep container in a well-ventilated place. Keep only in the original container in a cool, well-ventilated place. Take precautionary measures against static discharges.

Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing. Materials to avoid: Acid. Base. Material, combustible. Oxidizing agents.

Further information on storage conditions

Keep away from sources of ignition - No smoking. Protect against: heat. Keep/Store only in original container.

SECTION 8: Exposure controls/personal protection

**Safety Data Sheet**

according to UK REACH Regulation

WS Alu-Kontakt-Farbe AK 7900

Revision date: 13.03.2025

Product code: 5790

Page 5 of 11

8.1. Control parameters**Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
7429-90-5	Aluminium metal, respirable dust	-	4		TWA (8 h)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray. Occupational exposure controls: Refer to chapter 7. No further action is necessary.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Framed glasses. Goggles.

Hand protection

Tested protective gloves are to be worn:
Suitable material: NBR (Nitrile rubber), Butyl rubber.
Thickness of glove material: >0,4mm
penetration time (maximum wearing period): >480min
DIN-/EN-Norms EN ISO 374

Skin protection

Suitable protective clothing: Lab apron.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation. insufficient absorption.

Environmental exposure controls

Refer to chapter 7 No further action is necessary.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	silver grey
Odour:	characteristic
Odour threshold:	not determined

Test method

Boiling point or initial boiling point and boiling range:	135 °C
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	8 vol. %
Flash point:	23 °C
Auto-ignition temperature:	260 °C

**Safety Data Sheet**

according to UK REACH Regulation

WS Alu-Kontakt-Farbe AK 7900

Revision date: 13.03.2025

Product code: 5790

Page 6 of 11

Vapour pressure: 9,3 hPa
(at 20 °C)

Density (at 20 °C): 0,959 g/cm³ DIN 53217

9.2. Other information**Other safety characteristics**

Solvent content: 62,5 %
VOC value 613,5
Solid content: 37,00 %
Flow time: 56 3 DIN 53211
(at 20 °C)

SECTION 10: Stability and reactivity**10.1. Reactivity**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.2. Chemical stability

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.3. Possibility of hazardous reactions

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard. Conditions to avoid:
In case of warming: Danger of bursting container.

10.5. Incompatible materials

Alkalis (alkalis). Acid. Oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Acute toxicity, oral. Acute toxicity, inhalant. Toxicological data are not available.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) 3,659 mg/l

**Safety Data Sheet**

according to UK REACH Regulation

WS Alu-Kontakt-Farbe AK 7900

Revision date: 13.03.2025

Product code: 5790

Page 7 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
100-41-4	ethylbenzene				
	oral	LD50 3500 mg/kg	Rat	GESTIS	
	dermal	LD50 15400 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 17,2 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
64742-48-9	Hydrocarbons, C9-C11, alkanes, aromatics < 2 %				
	oral	LD50 5001 mg/kg	Rat		
	dermal	LD50 2001 mg/kg	Rat		
	Hydrocarbons Liquid, C10-C13,				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 >5000 mg/kg	Rabbit		
	Hydrocarbons, C9-C12, n-alkanes, cyclics, aromatics (<2%)				
	oral	LD50 15001 mg/kg	Rat		
	dermal	LD50 5001 mg/kg	Rabbit		
	inhalation (4 h) vapour	LC50 5001 mg/l	Rat		

Irritation and corrosivity

Caution if victim vomits: Risk of aspiration! After skin contact: irritant. Evaluation: non-irritant.

Specific effects in experiment on an animal

Rat LD50: 4300 - 5800 mg/kg Acute toxicity, oral

Data apply to the main component.

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

11.2. Information on other hazards**Further information**

Toxicological data are not available.

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Doesn't get into the sewage water as long as the process is carried out according to regulations.

Very toxic for Water fleas.

**Safety Data Sheet**

according to UK REACH Regulation

WS Alu-Kontakt-Farbe AK 7900

Revision date: 13.03.2025

Product code: 5790

Page 8 of 11

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
100-41-4	ethylbenzene					
	Acute fish toxicity	LC50	4,2 mg/l	96 h	Oncorhynchus mykiss	ECHA
	Acute algae toxicity	ErC50	3,6 mg/l	96 h	Algen	GESTIS

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
100-41-4	ethylbenzene	3,15

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

No data available

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Hand over to officially registered waste disposal company.

**Safety Data Sheet**

according to UK REACH Regulation

WS Alu-Kontakt-Farbe AK 7900

Revision date: 13.03.2025

Product code: 5790

Page 9 of 11

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:** UN 1263**14.2. UN proper shipping name:** PAINT**14.3. Transport hazard class(es):** 3**14.4. Packing group:** III

Hazard label: 3



Classification code: F1

Special Provisions: 163 367 650

Limited quantity: 5 L

Excepted quantity: E1

Transport category: 3

Hazard No: 30

Tunnel restriction code: D/E

Inland waterways transport (ADN)**14.1. UN number or ID number:** UN 1263**14.2. UN proper shipping name:** Paint**14.3. Transport hazard class(es):** 3**14.4. Packing group:** III

Hazard label: 3



Classification code: F1

Special Provisions: 163 367 650

Limited quantity: 5 L

Excepted quantity: E1

Marine transport (IMDG)**14.1. UN number or ID number:** UN 1263**14.2. UN proper shipping name:** PAINT**14.3. Transport hazard class(es):** 3**14.4. Packing group:** III

Hazard label: 3



Special Provisions: 163, 223, 367, 955

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:** UN 1263**14.2. UN proper shipping name:** PAINT**14.3. Transport hazard class(es):** 3**14.4. Packing group:** III

Hazard label: 3

**Safety Data Sheet**

according to UK REACH Regulation

WS Alu-Kontakt-Farbe AK 7900

Revision date: 13.03.2025

Product code: 5790

Page 10 of 11



Special Provisions:	A3 A72 A192	
Limited quantity Passenger:	10 L	
Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:		355
IATA-max. quantity - Passenger:		60 L
IATA-packing instructions - Cargo:		366
IATA-max. quantity - Cargo:		220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes

**14.6. Special precautions for user**

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes:	62,5 % VOC value 613,5
--	---------------------------

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Water hazard class (D):	2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Abbreviations and acronyms**

Water-react: Substances and mixtures which in contact with water emit flammable gases
Flam. Liq: Flammable liquids
Flam. Sol: Flammable solids
Acute Tox: Acute toxicity
Asp. Tox: Aspiration hazard
Skin Irrit: Skin irritation
Eye Irrit: Eye irritation
STOT SE: Specific target organ toxicity - single exposure
STOT RE: Specific target organ toxicity - repeated exposure
Aquatic Chronic: Chronic aquatic hazard

**Safety Data Sheet**

according to UK REACH Regulation

WS Alu-Kontakt-Farbe AK 7900

Revision date: 13.03.2025

Product code: 5790

Page 11 of 11

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H227	Combustible liquid.
H228	Flammable solid.
H261	In contact with water releases flammable gases.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H316	Causes mild skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The product is classified and labelled according to EC directives or corresponding national laws.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)