

**Safety Data Sheet**

according to UK REACH Regulation

PUR-Acryl Streichlack 2201, SG

Revision date: 13.03.2025

Product code: 7221

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

PUR-Acryl Streichlack 2201, SG

UFI: UX06-K96X-WVJV-RTH2

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**industrial paint
Paint, Varnish.**Uses advised against**

Do not use for products which come into contact with the food stuffs.

1.3. Details of the supplier of the safety data sheet

Company name:	W+S GmbH Lackchemie und Aerosol-Technik	
Street:	Am Sportplatz 5	
Place:	D-63791 Karlstein-Dettingen	
Telephone:	+49 6188 9575-0	Telefax: +49 6188 9575-30
E-mail:	info@ws-lackchemie.de	
Contact person:	Abt. Produkt / Sicherheit	
Responsible Department:	Abt. Produkt / Sicherheit	

1.4. Emergency telephone number: +49 551-19240 GIZ-Nord Poisons Centre**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GB CLP Regulation**Hazard categories:
Flammable liquids: Flam. Liq. 3
Hazardous to the aquatic environment: Aquatic Chronic 3
Hazard Statements:
Flammable liquid and vapour.
Harmful to aquatic life with long lasting effects.**2.2. Label elements****GB CLP Regulation****Signal word:** Warning**Pictograms:****Hazard statements**H226 Flammable liquid and vapour.
H412 Harmful to aquatic life with long lasting effects.**Precautionary statements**P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P273 Avoid release to the environment.
P370+P378 In case of fire: Use sand, dry chemical or alcohol-resistant foam to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.

**Safety Data Sheet**

according to UK REACH Regulation

PUR-Acryl Streichlack 2201, SG

Revision date: 13.03.2025

Product code: 7221

Page 2 of 10

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-95-6	Lösungsmittelnaphta, leichte aromatische, Benzolgehalt <0,1%			5 - < 10 %
	918-668-5		01-2119455851-35	
	Flam. Liq. 3, STOT SE 3, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H226 H335 H304 H411 EUH066			
64742-48-9	Naphtha (petroleum), hydrotreated heavy; Low boiling point hydrogen treated naphtha			5 - < 10 %
	265-150-3			
	Asp. Tox. 1; H304 EUH066			
112-07-2	2-butoxyethyl acetate; butylglycol acetate			5 - < 10 %
	203-933-3	607-038-00-2		
	Acute Tox. 4, Acute Tox. 4; H332 H312			
108-65-6	2-methoxy-1-methylethyl acetate			5 - < 10 %
	203-603-9	607-195-00-7		
	Flam. Liq. 3; H226			
123-86-4	n-butyl acetate			1 - < 5 %
	204-658-1	607-025-00-1		
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
1330-20-7	xylene			1 - < 5 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
64742-95-6	918-668-5	Lösungsmittelnaphta, leichte aromatische, Benzolgehalt <0,1%	5 - < 10 %
		inhalation: LC50 = 5,2 mg/l (vapours); dermal: LD50 = 3160 mg/kg; oral: LD50 = 2000 mg/kg	
112-07-2	203-933-3	2-butoxyethyl acetate; butylglycol acetate	5 - < 10 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 1500 mg/kg	
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	5 - < 10 %
		dermal: LD50 = 7500 mg/kg; oral: LD50 = 8532 mg/kg	
1330-20-7	215-535-7	xylene	1 - < 5 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg	

Further Information

Full text of R-phrases: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures**

**Safety Data Sheet**

according to UK REACH Regulation

PUR-Acryl Streichlack 2201, SG

Revision date: 13.03.2025

Product code: 7221

Page 3 of 10

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Give nothing to eat or drink.

After inhalation

In case of inhaling spray mists, consult a doctor immediately and show him box or label. If victim is at risk of losing consciousness, position and transport on their side. Provide fresh air.

After contact with skin

Wash with plenty of water. Remove contaminated, saturated clothing immediately. Change contaminated clothing. Wash thoroughly the body (shower or bath).

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Foam. Dry extinguishing powder. Carbon dioxide (CO₂). ABC powder.

Unsuitable extinguishing media

Water. High power water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Contaminated fire-fighting water must be collected separately. Remove product from area of fire. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Treat the recovered material as prescribed in the section on waste disposal.

**Safety Data Sheet**

according to UK REACH Regulation

PUR-Acryl Streichlack 2201, SG

Revision date: 13.03.2025

Product code: 7221

Page 4 of 10

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Preventive measures: If handled uncovered, arrangements with local exhaust ventilation have to be used. It is recommended to design all work processes always so that the following is excluded: inhalation. skin contact.

Eye contact. Take precautionary measures against static discharges.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Change contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.

Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking. Keep only in the original container in a cool, well-ventilated place. Take precautionary measures against static discharges.

Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing. Materials to avoid: Acid. Base. Material, combustible. Oxidizing agents.

Further information on storage conditions

Keep away from sources of ignition - No smoking. Protect against: heat. Keep/Store only in original container.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
112-07-2	2-Butoxyethyl acetate	20	133		TWA (8 h)	WEL
		50	332		STEL (15 min)	WEL
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls**Appropriate engineering controls**

Occupational exposure controls: Refer to chapter 7. No further action is necessary.

**Safety Data Sheet**

according to UK REACH Regulation

PUR-Acryl Streichlack 2201, SG

Revision date: 13.03.2025

Product code: 7221

Page 5 of 10

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Framed glasses. Goggles.

Hand protection

Tested protective gloves are to be worn:

Suitable material: NBR (Nitrile rubber), Butyl rubber.

Thickness of glove material: >0,4mm

penetration time (maximum wearing period): >480min

DIN-/EN-Norms EN ISO 374

Skin protection

Suitable protective clothing: Lab apron.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation, insufficient absorption.

Environmental exposure controls

Refer to chapter 7 No further action is necessary.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	characteristic
Odour:	hydrocarbons, aromatic.
Odour threshold:	not determined

Test method

Boiling point or initial boiling point and boiling range:	135 °C
Lower explosion limits:	1,7 vol. %
Upper explosion limits:	10,5 vol. %
Flash point:	30 °C
Auto-ignition temperature:	315 °C
Vapour pressure:	15 hPa
(at 20 °C)	
Density (at 20 °C):	1,483 g/cm ³ DIN 53217

9.2. Other information**Other safety characteristics**

Solvent content:	VOCV (CH): 24,4 %
	VOC (EU): 361,4 g/l
Solid content:	75,6 %
Softening point:	DIN 52025
Flow time:	315 (4 mm)
(at 20 °C)	

SECTION 10: Stability and reactivity**10.1. Reactivity**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.2. Chemical stability

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.3. Possibility of hazardous reactions

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

**Safety Data Sheet**

according to UK REACH Regulation

PUR-Acryl Streichlack 2201, SG

Revision date: 13.03.2025

Product code: 7221

Page 6 of 10

10.4. Conditions to avoid

Keep away from heat. Ignition hazard. Conditions to avoid:
In case of warming: Danger of bursting container.

10.5. Incompatible materials

Alkalis (alkalis). Acid. Oxidizing agents.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Toxicological data are not available.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
64742-95-6	Lösungsmittelnaphtha, leichte aromatische, Benzolgehalt <0,1%				
	oral	LD50 2000 mg/kg	Rat		
	dermal	LD50 3160 mg/kg	Rabbit.		
	inhalation (4 h) vapour	LC50 5,2 mg/l	Rat		
112-07-2	2-butoxyethyl acetate; butylglycol acetate				
	dermal	LD50 1500 mg/kg	Rabbit	RTECS	
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 8532 mg/kg	Rat	RTECS	
	dermal	LD50 7500 mg/kg	Rabbit		
1330-20-7	xylene				
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			

Irritation and corrosivity

Evaluation: non-irritant.

STOT-repeated exposure

Has de-greasing effect on the skin.

Specific effects in experiment on an animal

Rat LD50: 4300 - 5800 mg/kg Acute toxicity, oral
Data apply to the main component.

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

**Safety Data Sheet**

according to UK REACH Regulation

PUR-Acryl Streichlack 2201, SG

Revision date: 13.03.2025

Product code: 7221

Page 7 of 10

11.2. Information on other hazards**Further information**

Toxicological data are not available.

SECTION 12: Ecological information**12.1. Toxicity**

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Doesn't get into the sewage water as long as the process is carried out according to regulations.

Very toxic for Water fleas.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
112-07-2	2-butoxyethyl acetate; butylglycol acetate					
	Acute algae toxicity	ErC50 > 500 mg/l	72 h	Desmodesmus subspicatus	IUCLID	
	Acute crustacea toxicity	EC50 37 mg/l	48 h	Daphnia magna		
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50 161 mg/l	96 h	Pimephales promelas		
	Acute crustacea toxicity	EC50 408 mg/l	48 h	Daphnia magna		

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
112-07-2	2-butoxyethyl acetate; butylglycol acetate	1,51
108-65-6	2-methoxy-1-methylethyl acetate	0,43

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

No data available

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC). Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

**Safety Data Sheet**

according to UK REACH Regulation

PUR-Acryl Streichlack 2201, SG

Revision date: 13.03.2025

Product code: 7221

Page 8 of 10

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself. Hand over to officially registered waste disposal company.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number: UN1263
14.2. UN proper shipping name: PAINT or PAINT RELATED MATERIAL
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 163 640E 650
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Other applicable information (land transport)

If this product is transported in containers of a maximum capacity of 450 l according to ADR/RID No. 2.2.3.1.5., it is not referred to as a dangerous good in terms of transport regulations.

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: III
Hazard label: 3



Classification code: F1
Special Provisions: 163 367 650
Limited quantity: 5 L
Excepted quantity: E1

**Safety Data Sheet**

according to UK REACH Regulation

PUR-Acryl Streichlack 2201, SG

Revision date: 13.03.2025

Product code: 7221

Page 9 of 10

Other applicable information (inland waterways transport)

If this product is transported in containers of a maximum capacity of 450 l according to ADR/RID No. 2.2.3.1.5., it is not referred to as a dangerous good in terms of transport regulations.

Marine transport (IMDG)**14.1. UN number or ID number:** UN 1263**14.2. UN proper shipping name:** PAINT**14.3. Transport hazard class(es):** 3**14.4. Packing group:** III

Hazard label: 3



Special Provisions: 163, 223, 367, 955

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-E, S-E

Other applicable information (marine transport)

Transport in accordance with paragraph 2.3.2.5 of the IMDG Code.

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:** UN 1263**14.2. UN proper shipping name:** PAINT**14.3. Transport hazard class(es):** 3**14.4. Packing group:** III

Hazard label: 3



Special Provisions: A3 A72 A192

Limited quantity Passenger: 10 L

Passenger LQ: Y344

Excepted quantity: E1

IATA-packing instructions - Passenger: 355

IATA-max. quantity - Passenger: 60 L

IATA-packing instructions - Cargo: 366

IATA-max. quantity - Cargo: 220 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in
paints and varnishes: VOCV (CH): 24,4 %
VOC (EU): 361,4 g/l

**Safety Data Sheet**

according to UK REACH Regulation

PUR-Acryl Streichlack 2201, SG

Revision date: 13.03.2025

Product code: 7221

Page 10 of 10

National regulatory information

Employment restrictions:

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water hazard class (D):

2 - obviously hazardous to water

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Abbreviations and acronyms**

Flam. Liq: Flammable liquids

Acute Tox: Acute toxicity

Asp. Tox: Aspiration hazard

Skin Irrit: Skin irritation

STOT SE: Specific target organ toxicity - single exposure

Aquatic Chronic: Chronic aquatic hazard

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The product is classified and labelled according to EC directives or corresponding national laws.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)