

**Safety Data Sheet**

according to UK REACH Regulation

WS-CorroXXan K3707

Revision date: 13.03.2025

Product code: 7377

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

WS-CorroXXan K3707

UFI: 0N16-M9R4-CVJU-1J5K

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**industrial paint
Paint, Varnish.**Uses advised against**

Do not use for products which come into contact with the food stuffs.

1.3. Details of the supplier of the safety data sheet

Company name: W+S GmbH Lackchemie und Aerosol-Technik
Street: Am Sportplatz 5
Place: D-63791 Karlstein-Dettingen
Telephone: +49 6188 9575-0
E-mail: info@ws-lackchemie.de
Contact person: Abt. Produkt / Sicherheit
Responsible Department: Abt. Produkt / Sicherheit

Telefax: +49 6188 9575-30

1.4. Emergency telephone number:

+49 551-19240 GIZ-Nord Poisons Centre

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard categories:

Flammable liquids: Flam. Liq. 3

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - repeated exposure: STOT RE 2

Hazard Statements:

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause damage to organs through prolonged or repeated exposure.

Harmful to aquatic life with long lasting effects.

2.2. Label elements**GB CLP Regulation****Hazard components for labelling**

xylene

Signal word: Warning

Pictograms:**Hazard statements**

H226

Flammable liquid and vapour.

H315

Causes skin irritation.

**Safety Data Sheet**

according to UK REACH Regulation

WS-CorroXXan K3707

Revision date: 13.03.2025

Product code: 7377

Page 2 of 13

H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing Gas/fumes/vapour/spray.
P370+P378	In case of fire: Use sand, dry chemical or alcohol-resistant foam to extinguish.
P271	Use only outdoors or in a well-ventilated area.

Special labelling of certain mixtures

EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
--------	--

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

**Safety Data Sheet**

according to UK REACH Regulation

WS-CorroXXan K3707

Revision date: 13.03.2025

Product code: 7377

Page 3 of 13

Relevant ingredients

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
1330-20-7	xylene			20 - < 25 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			
108-65-6	2-methoxy-1-methylethyl acetate			1 - < 5 %
	203-603-9	607-195-00-7		
	Flam. Liq. 3; H226			
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether			1 - < 5 %
	203-539-1	603-064-00-3		
	Flam. Liq. 3, STOT SE 3; H226 H336			
100-41-4	ethylbenzene			1 - < 5 %
	202-849-4	601-023-00-4		
	Flam. Liq. 2, Acute Tox. 4, STOT RE 2, Asp. Tox. 1; H225 H332 H373 H304			
13463-67-7	titanium dioxide			1 - < 5 %
	236-675-5	022-006-00-2		
	Carc. 2; H351			
64742-48-9	Hydrocarbons, C9-C11, alkanes, aromatics < 2 %			1 - < 5 %
	919-857-5		01-2119463258-33	
	Flam. Liq. 3, STOT SE 3, Asp. Tox. 1; H226 H336 H304			
85711-46-2	Fatty acids, C14-18 and C16-18-unsatd., maleated			< 1 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1B; H315 H319 H317			
1474044-65-9	Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates			< 1 %
	939-607-9			
	Acute Tox. 3, Acute Tox. 4, Skin Corr. 1C, Eye Dam. 1, Aquatic Chronic 1; H311 H302 H314 H318 H410			
136-53-8	Zincbis(2-Ethylhexanoate)			< 1 %
	205-251-1			
	Repr. 2, Eye Irrit. 2, Aquatic Chronic 3; H361 H319 H412			
149-57-5	2-ethylhexanoic acid			< 1 %
	205-743-6	607-230-00-6		
	Repr. 1B; H360D			
1314-13-2	zinc oxide			< 1 %
	215-222-5	030-013-00-7		
	Aquatic Acute 1, Aquatic Chronic 1; H400 H410			
136-52-7	Cobaltbis(2-Ethylhexanoate)			< 1 %
	205-250-6		01-2119524678-29	
	Repr. 1B, Eye Irrit. 2, Skin Sens. 1, Aquatic Acute 1, Aquatic Chronic 3; H360FD H319 H317 H400 H412			
108-31-6	maleic anhydride			< 1 %
	203-571-6	607-096-00-9		
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1A, STOT RE 1; H302 H314 H318 H334 H317 H372 EUH071			

**Safety Data Sheet**

according to UK REACH Regulation

WS-CorroXXan K3707

Revision date: 13.03.2025

Product code: 7377

Page 4 of 13

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
Specific Conc. Limits, M-factors and ATE			
1330-20-7	215-535-7	xylene	20 - < 25 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg	
108-65-6	203-603-9	2-methoxy-1-methylethyl acetate	1 - < 5 %
		dermal: LD50 = 7500 mg/kg; oral: LD50 = 8532 mg/kg	
107-98-2	203-539-1	1-methoxy-2-propanol; monopropylene glycol methyl ether	1 - < 5 %
		dermal: LD50 = 11000 mg/kg; oral: LD50 = > 5000 mg/kg	
100-41-4	202-849-4	ethylbenzene	1 - < 5 %
		inhalation: LC50 = 17,2 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: LD50 = 15400 mg/kg; oral: LD50 = 3500 mg/kg	
64742-48-9	919-857-5	Hydrocarbons, C9-C11, alkanes, aromatics < 2 %	1 - < 5 %
		dermal: LD50 = 2001 mg/kg; oral: LD50 = 5001 mg/kg	
1474044-65-9	939-607-9	Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates	< 1 %
		dermal: ATE = 300 mg/kg; oral: ATE = 500 mg/kg	
149-57-5	205-743-6	2-ethylhexanoic acid	< 1 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 3000 mg/kg	
1314-13-2	215-222-5	zinc oxide	< 1 %
		oral: LD50 = > 5000 mg/kg	
108-31-6	203-571-6	maleic anhydride	< 1 %
		dermal: LD50 = 2620 mg/kg; oral: LD50 = 400 mg/kg Skin Sens. 1A; H317: >= 0,001 - 100	

Further Information

Full text of R-phrases: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Give nothing to eat or drink.

After inhalation

In case of inhaling spray mists, consult a doctor immediately and show him box or label. If victim is at risk of losing consciousness, position and transport on their side. Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing. Medical treatment necessary.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Give nothing to eat or drink. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Frequently or prolonged contact with skin may cause dermal irritation.

4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

**Safety Data Sheet**

according to UK REACH Regulation

WS-CorroXXan K3707

Revision date: 13.03.2025

Product code: 7377

Page 5 of 13

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water. Carbon dioxide (CO₂). Foam. Extinguishing powder.**Unsuitable extinguishing media**

High power water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke. In case of fire and/or explosion do not breathe fumes. Use water spray jet to protect personnel and to cool endangered containers. Contaminated fire-fighting water must be collected separately.

5.3. Advice for firefighters

Use appropriate respiratory protection.

Additional information

Contaminated fire-fighting water must be collected separately. Remove product from area of fire. Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Keep container in a well-ventilated place.

Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing.

**Safety Data Sheet**

according to UK REACH Regulation

WS-CorroXXan K3707

Revision date: 13.03.2025

Product code: 7377

Page 6 of 13

Further information on storage conditions

Keep away from sources of ignition - No smoking. Protect against: heat. Keep/Store only in original container.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL
108-65-6	1-Methoxypropyl acetate	50	274		TWA (8 h)	WEL
		100	548		STEL (15 min)	WEL
100-41-4	Ethylbenzene	100	441		TWA (8 h)	WEL
		125	552		STEL (15 min)	WEL
108-31-6	Maleic anhydride	-	1		TWA (8 h)	WEL
		-	3		STEL (15 min)	WEL
13463-67-7	Titanium dioxide, respirable	-	4		TWA (8 h)	WEL
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid (creatinine)	650 mmol/mol	urine	Post shift

8.2. Exposure controls**Appropriate engineering controls**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Suitable eye protection: Framed glasses. Goggles.

Hand protection

Tested protective gloves are to be worn:

Suitable material: NBR (Nitrile rubber), Butyl rubber.

Thickness of glove material: >0,4mm

penetration time (maximum wearing period): >480min

DIN-/EN-Norms EN ISO 374

Skin protection

Suitable protective clothing: Lab apron.

Respiratory protection

Respiratory protection necessary at: exceeding exposure limit values insufficient ventilation, insufficient absorption.

Environmental exposure controls

Refer to chapter 7 No further action is necessary.

**Safety Data Sheet**

according to UK REACH Regulation

WS-CorroXXan K3707

Revision date: 13.03.2025

Product code: 7377

Page 7 of 13

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	liquid
Colour:	characteristic
Odour:	hydrocarbons, aromatic.
Odour threshold:	not determined

Test method

Boiling point or initial boiling point and boiling range:	124 °C
Lower explosion limits:	1,1 vol. %
Upper explosion limits:	7 vol. %
Flash point:	24 °C
Auto-ignition temperature:	315 °C
Vapour pressure:	12 hPa
(at 20 °C)	
Density:	1,277 g/cm ³

9.2. Other information**Other safety characteristics**

Solvent content:	VOCV (CH): 40,4%
	VOC (EU): 515,9 g/l
Solid content:	59,6
Softening point:	DIN 52025
Flow time:	290 s 4 DIN 53211
(at 20 °C)	

SECTION 10: Stability and reactivity**10.1. Reactivity**

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.2. Chemical stability

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.3. Possibility of hazardous reactions

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.6. Hazardous decomposition products

Thermal decomposition can lead to the escape of irritating gases and vapors.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in GB CLP Regulation****Acute toxicity**

Acute toxicity, oral. Acute toxicity, inhalant. Toxicological data are not available.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

**Safety Data Sheet**

according to UK REACH Regulation

WS-CorroXXan K3707

Revision date: 13.03.2025

Product code: 7377

Page 8 of 13

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
1330-20-7	xylene				
	dermal	ATE 1100 mg/kg			
	inhalation vapour	ATE 11 mg/l			
	inhalation dust/mist	ATE 1,5 mg/l			
108-65-6	2-methoxy-1-methylethyl acetate				
	oral	LD50 8532 mg/kg	Rat	RTECS	
	dermal	LD50 7500 mg/kg	Rabbit		
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether				
	oral	LD50 > 5000 mg/kg	Rat	IUCLID	
	dermal	LD50 11000 mg/kg	Rabbit		
100-41-4	ethylbenzene				
	oral	LD50 3500 mg/kg	Rat	GESTIS	
	dermal	LD50 15400 mg/kg	Rabbit	GESTIS	
	inhalation (4 h) vapour	LC50 17,2 mg/l	Rat		
	inhalation dust/mist	ATE 1,5 mg/l			
64742-48-9	Hydrocarbons, C9-C11, alkanes, aromatics < 2 %				
	oral	LD50 5001 mg/kg	Rat		
	dermal	LD50 2001 mg/kg	Rat		
1474044-65-9	Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates				
	oral	ATE 500 mg/kg			
	dermal	ATE 300 mg/kg			
149-57-5	2-ethylhexanoic acid				
	oral	LD50 3000 mg/kg	Rat		
	dermal	LD50 > 2000 mg/kg	Rabbit		
1314-13-2	zinc oxide				
	oral	LD50 > 5000 mg/kg	Rat	IUCLID	
108-31-6	maleic anhydride				
	oral	LD50 400 mg/kg	Rat	GESTIS	
	dermal	LD50 2620 mg/kg	Rabbit	GESTIS	

Irritation and corrosivity

After skin contact: irritant.

**Safety Data Sheet**

according to UK REACH Regulation

WS-CorroXXan K3707

Revision date: 13.03.2025

Product code: 7377

Page 9 of 13

Specific effects in experiment on an animal

Rat LD50: 4300 - 5800 mg/kg Acute toxicity, oral

Data apply to the main component.

Additional information on tests

The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

11.2. Information on other hazards**Further information**

Toxicological data are not available.

SECTION 12: Ecological information**12.1. Toxicity**

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
108-65-6	2-methoxy-1-methylethyl acetate					
	Acute fish toxicity	LC50 161 mg/l	96 h	Pimephales promelas		
	Acute crustacea toxicity	EC50 408 mg/l	48 h	Daphnia magna		
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether					
	Acute fish toxicity	LC50 4600 - 10000 mg/l	96 h	Leuciscus idus	IUCLID	
	Acute algae toxicity	ErC50 > 1000 mg/l	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 > 500 mg/l	48 h	Daphnia magna	IUCLID	
100-41-4	ethylbenzene					
	Acute fish toxicity	LC50 4,2 mg/l	96 h	Oncorhynchus mykiss	ECHA	
	Acute algae toxicity	ErC50 3,6 mg/l	96 h	Algen	GESTIS	
149-57-5	2-ethylhexanoic acid					
	Acute fish toxicity	LC50 > 250 mg/l	96 h	Leuciscus idus	ECHA	
	Acute algae toxicity	ErC50 61 mg/l	72 h	Algae	ECHA	
	Acute crustacea toxicity	EC50 85,4 mg/l	48 h	Daphnia magna	ECHA	
108-31-6	maleic anhydride					
	Acute algae toxicity	ErC50 29 mg/l	72 h	Desmodesmus subspicatus	IUCLID	

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

No data available

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-65-6	2-methoxy-1-methylethyl acetate	0,43
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	-0,437
100-41-4	ethylbenzene	3,15
149-57-5	2-ethylhexanoic acid	2,7

12.4. Mobility in soil

No data available

**Safety Data Sheet**

according to UK REACH Regulation

WS-CorroXXan K3707

Revision date: 13.03.2025

Product code: 7377

Page 10 of 13

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

No data available

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available

Further information

Do not allow to enter into surface water or drains. The classification was carried out according to the calculation method of the Preparations Directive (1999/45/EC).

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances; hazardous waste

Contaminated packaging

Hand over to officially registered waste disposal company.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 1263

14.2. UN proper shipping name:

PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es):

3

14.4. Packing group:

III

Hazard label:

3



Classification code:

F1

Special Provisions:

163 367 650

Limited quantity:

LQ7

Excepted quantity:

E1

Transport category:

3

Hazard No:

30

**Safety Data Sheet**

according to UK REACH Regulation

WS-CorroXXan K3707

Revision date: 13.03.2025

Product code: 7377

Page 11 of 13

Tunnel restriction code: D/E

Other applicable information (land transport)

Special provisions: 163 640E 650

E1

: 3

If this product is transported in containers of a maximum capacity of 450 l according to ADR/RID No. 2.2.3.1.5., it is not referred to as a dangerous good in terms of transport regulations.

Inland waterways transport (ADN)**14.1. UN number or ID number:** UN 1263**14.2. UN proper shipping name:** Paint**14.3. Transport hazard class(es):** 3**14.4. Packing group:** III

Hazard label: 3



Classification code: F1

Special Provisions: 163 367 650

Limited quantity: 5 L

Excepted quantity: E1

Other applicable information (inland waterways transport)

If this product is transported in containers of a maximum capacity of 450 l according to ADR/RID No. 2.2.3.1.5., it is not referred to as a dangerous good in terms of transport regulations.

Marine transport (IMDG)**14.1. UN number or ID number:** UN 1263**14.2. UN proper shipping name:** PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base)**14.3. Transport hazard class(es):** 3**14.4. Packing group:** III

Hazard label: 3



Marine pollutant: •

Special Provisions: 163, 223, 367, 955

Limited quantity: 5 L

Excepted quantity: E1

EmS: F-E, S-E

Other applicable information (marine transport)

Special provisions: 163, 223, 944, 955

E1

Air transport (ICAO-TI/IATA-DGR)**14.1. UN number or ID number:** UN 1263**14.2. UN proper shipping name:** PAINT (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler and liquid lacquer base)**14.3. Transport hazard class(es):** 3**14.4. Packing group:** III

Hazard label: 3



**Safety Data Sheet**

according to UK REACH Regulation

WS-CorroXXan K3707

Revision date: 13.03.2025

Product code: 7377

Page 12 of 13

Special Provisions:	A3 A72 A192	
Limited quantity Passenger:	10 L	
Passenger LQ:	Y344	
Excepted quantity:	E1	
IATA-packing instructions - Passenger:		309
IATA-max. quantity - Passenger:		60 L
IATA-packing instructions - Cargo:		310
IATA-max. quantity - Cargo:		220 L

Other applicable information (air transport)

E1

: Y309

Special provisions: A3 A72

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40, Entry 75

Directive 2004/42/EC on VOC in paints and varnishes:	VOCV (CH): 40,4% VOC (EU): 515,9 g/l
---	---

National regulatory information

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
--------------------------	---

Water hazard class (D):	2 - obviously hazardous to water
-------------------------	----------------------------------

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Abbreviations and acronyms**

Flam. Liq: Flammable liquids
Acute Tox: Acute toxicity
Asp. Tox: Aspiration hazard
Skin Corr: Skin corrosion
Skin Irrit: Skin irritation
Eye Dam: Eye damage
Eye Irrit: Eye irritation
Resp. Sens: Respiratory sensitisation
Skin Sens: Skin sensitisation
Carc: Carcinogenicity
Repr: Reproductive toxicity
STOT SE: Specific target organ toxicity - single exposure
STOT RE: Specific target organ toxicity - repeated exposure
Aquatic Acute: Acute aquatic hazard
Aquatic Chronic: Chronic aquatic hazard

Relevant H and EUH statements (number and full text)

**Safety Data Sheet**

according to UK REACH Regulation

WS-CorroXXan K3707

Revision date: 13.03.2025

Product code: 7377

Page 13 of 13

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H360D	May damage the unborn child.
H360FD	May damage fertility. May damage the unborn child.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Further Information

The product is classified and labelled according to EC directives or corresponding national laws.

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)